PHILIPS

Philips V Line 271V8LAB/00 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips Product family: V Line Product code: 271V8LAB/00

Product name: 271V8LAB/00

Monitor 271V8LAB LCD monitor

NVIDIA G-SYNC *

Philips V Line 271V8LAB/00 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black:

This monitor gives an unmatched viewing experience. Not only is it equipped with essential features, but it also has ones that stand out like its 100 Hz refresh rate, Adaptive Sync, LowBlue Mode, flicker-free, a VESA mount and more.

Philips V Line 271V8LAB/00. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black





| Display | | Ergonomics | |
|---|---|---|---|
| Display diagonal * 68.6 cm (27") Display resolution * 1920 x 1080 pixels HD type * Full HD Native aspect ratio * 16:9 Display technology * LCD Panel type * VA Backlight type W-LED Touchscreen * X Display brightness (typical) 250 cd/m² Response time 4 ms Anti-glare screen | 1920 x 1080 pixels Full HD 16:9 LCD VA W-LED 250 cd/m² 4 ms | VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Tilt angle range On Screen Display (OSD) languages | 100 x 100 mm Kensington -5 - 20° Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian |
| Screen shape * Contrast ratio (typical) * | Flat 4000:1 | LED indicators Power | Operation, Stand-by |
| Dynamic contrast ratio marketing name Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Pixel density Horizontal scan range | Mega Infinity DCR 100 Hz 178° 178° 16.7 million colours 0.3114 x 0.3114 mm 82 ppi 30 - 115 kHz | Energy efficiency class (SDR) * Energy efficiency class (HDR) * Power consumption (typical) * Power consumption (standby) * Power consumption (off) AC input voltage AC input frequency Power supply type | Not available Not available 32.89 W 0.5 W 0.3 W 100 - 240 V 50/60 Hz Internal |
| Vertical scan range | 48 - 100 Hz | Operational conditions | |
| Viewable size, horizontal 59.8 cm Viewable size, vertical 33.6 cm Display diagonal (metric) 68.6 cm DDC/CI Haze rate 25% Surface hardness 3H | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Non-operating altitude | 0 - 40 °C -20 - 60 °C 20 - 80% 0 - 3658 m 0 - 12192 m | |
| Colour depth | 8 bit | Packaging content | |
| Display sRGB Performance | √ | Stand included Manual | 1 |
| | | | |

| Performance | | Weight & dimensions | |
|-----------------------------|------------------------------------|-----------------------------------|--|
| AMD FreeSync * | × | Width (with stand) | 614 mm |
| VESA Adaptive Sync support | ✓ | Depth (with stand) | 231 mm |
| Component video sync | Separate sync, Sync-on-green (SOG) | Height (with stand) | 457 mm |
| Flicker-free technology | (300) | Weight (with stand) | 3.74 kg |
| Low Blue Light technology | 1 | Width (without stand) | 614 mm |
| 5 57 | • | Depth (without stand) | 53 mm |
| Multimedia | | Height (without stand) | 367 mm |
| Built-in speaker(s) * | ✓ | Weight (without stand) | 3.28 kg |
| Built-in camera * | × | Packaging data | |
| Number of speakers | 2 | Package width | 730 mm |
| RMS rated power | 4 W | Package depth | 123 mm |
| Design | | Package height | 446 mm |
| Market positioning * | Home | Package weight | 5.35 kg |
| Product colour * | Black | Sustainability | |
| Ports & interfaces | | Doesn't contain | Mercury, PVC/BFR |
| Built-in USB hub * | X | Other features | |
| VGA (D-Sub) ports quantity | 1 | Exterior finish type | Textured |
| HDMI * | ✓ | Picture enhancement | SmartImage |
| HDMI ports quantity | 1 | Recyclable packaging material | 100% |
| HDMI version | 1.4 | | CB; CE Mark; CCC; CECP; CEL; |
| Audio output PC Audio in | 1 | Regulatory Approvals | ICES-003; BSMI; EAC; FCC; PSB; TUV Ergo; TUV/GS |
| HDCP | · | EasyRead mode | ✓ |
| HDCP version | 1.4 | LowBlue mode | ✓ |
| | | Mean time between failures (MTBF) | 30000 h |



8712581804374

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.