

TP-Link Omada PoE+ Injector

Brand : TP-Link Product family: Omada Product code: POE160S

Product name: PoE+ Injector

- 2 Gigabit ports ensure faster transmission
- Complies with IEEE802.3af/at standards, supplies up to 30 $\ensuremath{\text{W}}$
- Reduces infrastructure costs by transmitting data and power simultaneously via an Ethernet cable
- Automatically determines and supplies the exact power to meet the device's need
- Wall-mounting and desktop design accommodates most installation scenarios
- Plug & Play installation, requires no configuration
- Integrated power supply

PoE+, 10/100/1000Mbps RJ45 In, 10/100/1000Mbps RJ45 Out, 125×59.4×36.8 mm

TP-Link Omada PoE+ Injector:

The PoE+ Injector POE160S (TL-POE160S) fully complies with IEEE 802.3af/at standards, and can work with all IEEE 802.3af/at PoE compliant PDs (Powered Devices) or PoE Receiver Adapters, such as TP-Link's POE10R (TL-POE10R), or other equivalent product, to expand your network to where there are no power line or outlet, where you wish to fix device such as AP, IP Camera or IP Phone, etc.



9	Ptp-link Omåda P00:1003 Put-1 hyecter	
		b

Network		Power		
Ethernet interface type	Gigabit Ethernet	AC adapter frequency	50/60 Hz	
Ethernet LAN data rates	10,100,1000 Mbit/s	Operational conditions		
Cabling technology Power over Ethernet (PoE) Networking standards Cable types supported	10/100/1000 ✓ IEEE 802.3ab, IEEE 802.3af, IEEE 802.3u, IEEE 802.3u Cat3, Cat4, Cat5, Cat5e	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 10 - 90% -40 - 70 °C 5 - 90%	
Features	,,,	Weight & dimensions		
Product colour Wall mountable Plug and Play	Black ✓	Width Depth Height	125 mm 59.4 mm 36.8 mm	
Maximum operating distance	100 m	Packaging data		
LED indicators	Power	Package type	Box	
Ports & interfaces		Packaging content		
Ethernet LAN (RJ-45) ports RJ-45 input ports RJ-45 output ports	2 1 1	Number of products included Wall mounting kit Power cord included	1 pc(s) ✓	
Power		Quick installation guide	✓	
Output power AC adapter input voltage	30 W 100 - 240 V			



8592978537609

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.