Gigabyte GAMING GeForce RTX 4070 SUPER OC 12G NVIDIA 12 GB GDDR6X

Brand : Gigabyte Product family: GAMING Product code: GV-N407SGAMING OC-12GD

Product name : GeForce RTX 4070 SUPER GAMING OC 12G

- Powered by NVIDIA DLSS 3, ultra-efficient Ada Lovelace arch, and full ray tracing
- 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
- 3rd Generation RT Cores: Up to 2X ray tracing performance
- Powered by GeForce RTX[™] 4070 SUPER
- Integrated with 12GB GDDR6X 192bit memory interface
- WINDFORCE cooling system
- RGB Fusion
- Dual BIOS
- Protection metal back plate
- 4 Years Warranty (Online registration required)

NVIDIA GeForce RTX 4070 SUPER, 12GB GDDR6X, 192 bit, 21000MHz, PCI Express 4.0, 1 x HDMI (2.1a), 3 x DP (1.4a), CUDA, DirectX 12 Ultimate, OpenGL 4.6

Gigabyte GAMING GeForce RTX 4070 SUPER OC 12G. Graphics processor family: NVIDIA, Graphics processor: GeForce RTX 4070 SUPER. Discrete graphics card memory: 12 GB, Graphics card memory type: GDDR6X, Memory bus: 192 bit, Memory clock speed: 21000 MHz. Maximum resolution: 7680 x 4320 pixels. DirectX version: 12 Ultimate, OpenGL version: 4.6. Interface type: PCI Express 4.0. Cooling type: Active, Number of fans: 3 fan(s)





Processor		Performance	
CUDA * Graphics processor family * Graphics processor *	NVIDIA GeForce RTX 4070 SUPER 7680 x 4320 pixels	DirectX version * OpenGL version * Dual Link DVI *	12 Ultimate 4.6
Maximum resolution *		Design	
Parallel processing technology support * Maximum displays per videocard	Not supported 4	Cooling type * Cooling technology	Active GIGABYTE WINDFORCE 3X
Memory	12 GB	Number of fans Form factor	3 fan(s) Full-Height/Full-Length (FH/FL)
Discrete graphics card memory * Graphics card memory type *	GDDR6X	Product colour Power	Black
Memory bus * Memory clock speed Memory bandwidth (max)	192 bit 21000 MHz 21 GB/s	Minimum system power supply * Supplementary power connectors	700 W 1x 16-pin
Ports & interfaces		Weight & dimensions	
Interface type * HDMI ports quantity * HDMI version	PCI Express 4.0 1 2.1a	Depth Height Width	300 mm 57.6 mm 130 mm
DisplayPorts quantity *	3	Packaging data	
DisplayPort version	1.4a	Package width	230 mm
Performance TV tuner integrated *	×	Package depth Package height Package weight Package type	398 mm 85 mm 194 g Box



4719331354152

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.