

## ASUS ProArt -RTX4070TIS-O16G NVIDIA GeForce RTX 4070 Ti SUPER 16 GB GDDR6X

**Brand :** ASUS

**Product family:** ProArt

**Product code:** 90YV0KJ0-M0NA00

**Product name :** PROART-RTX4070TIS-O16G



- NVIDIA Studio: RTX and AI-accelerated creator apps, exclusive AI software, and Studio Drivers for unmatched creativity and performance
- NVIDIA Ada Lovelace Streaming Multiprocessors: Up to 2x performance and power efficiency
- 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
- 3rd Generation RT Cores: Up to 2x ray tracing performance
- OC mode: 2670 MHz (OC mode)/ 2640 MHz (Default mode)
- Axial-tech fans scaled up for 21% more airflow
- 2.5-slot design: allows for greater build compatibility while maintaining premium cooling
- Dual Ball Fan Bearings last up to twice as long as conventional designs
- Auto-Extreme precision automated manufacturing for higher reliability
- GPU Tweak III profile Connect enables creators to seamlessly optimize system performance and cooling for every app

ProArt GeForce RTX 4070 Ti SUPER OC Edition 16GB GDDR6X brings elegant and minimalist style to empower creator PC builds with full-scale GeForce RTX 40 SUPER Series performance.



Processor		Performance	
CUDA *	✓	TV tuner integrated *	✗
CUDA cores	8448	DirectX version *	12 Ultimate
Graphics processor family *	NVIDIA	OpenGL version *	4.6
Graphics processor *	GeForce RTX 4070 Ti SUPER	HDCP	✓
Processor boost clock speed	2640 MHz	HDCP version	2.3
Processor frequency (OC mode)	2670 MHz	Dual Link DVI *	✗
Maximum resolution *	7680 x 4320 pixels	NVIDIA G-SYNC	✓
Parallel processing technology support *	Not supported	NVIDIA Ansel	✓
Maximum displays per videocard	4	Design	
Memory		Cooling type *	Active
Discrete graphics card memory *	16 GB	Number of fans	3 fan(s)
Graphics card memory type *	GDDR6X	Form factor	Full-Height/Full-Length (FH/FL)
Memory bus *	256 bit	Number of slots	2.5
Data transfer rate	21 Gbit/s	Product colour	Black
Ports & interfaces		Power	
Interface type *	PCI Express 4.0	Minimum system power supply *	750 W
HDMI ports quantity *	1	Supplementary power connectors	1x 16-pin
HDMI version	2.1a	Weight & dimensions	
DisplayPorts quantity *	3	Depth	300 mm
DisplayPort version	1.4a	Height	50 mm
		Width	120 mm
		Packaging data	
		Package type	Box



4711387471838

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-JUN-2024. Prints or copies of Information are only valid on the printed Publication date