iiyama

iiyama ProLite T2752MSC-B1 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Touchscreen Black

Brand : iiyama   **Product family:** ProLite   **Product code:** T2752MSC-B1

Product name : T2752MSC-B1

27", 10 point touch, 1920 x 1080, 16:9, 1000:1
iiyama ProLite T2752MSC-B1. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black

Display

Display diagonal *	68.6 cm (27")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Touchscreen *	✓
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (peak)	400 cd/m²
Display brightness (typical)	360 cd/m²
Response time	5 ms
Screen shape *	Flat
Aspect ratio	16:9
Contrast ratio (typical) *	1000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.311 x 0.311 mm
Horizontal scan range	30 - 83 kHz
Viewable size, horizontal	59.8 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.6 cm
Display brightness	255 cd/m²

Performance

NVIDIA G-SYNC *	✗
AMD FreeSync *	✗
Windows operating systems supported	✓
Linux operating systems supported	✓

Multimedia

Built-in speaker(s) *	✓
Built-in camera *	✗
Number of speakers	2
RMS rated power	1 W

Design

Market positioning *	Business
Product colour *	Black
Glass thickness	2.2 mm

Ports & interfaces

USB Type-A downstream ports quantity	3
USB Touch port	✓
HDMI *	✓
HDMI ports quantity	1
DisplayPorts quantity	1
Audio output	✓
HDCP	✓

Network

Ethernet LAN	✗

Ergonomics

VESA mounting *	✓
Panel mounting interface	100 x 100 mm
Wall mountable	✓
Cable lock slot *	✓
Cable lock slot type	Kensington
Tilt adjustment	✓
Tilt angle range	5 - 90°
On Screen Display (OSD) languages	German, Dutch, English, Spanish, French, Italian, Japanese, Polish, Portuguese, Russian
Number of OSD languages	10
Plug and Play	✓
LED indicators	✓

Power

Energy efficiency class (SDR) *	E
Power consumption (typical) *	30 W
Power consumption (standby) *	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50 Hz
Energy efficiency scale	A to G

Packaging content

Cables included	AC, HDMI, USB
Quick start guide	✓

Weight & dimensions

Width (with stand)	614 mm
Depth (with stand)	239.5 mm
Height (with stand)	403 mm
Weight (with stand)	6.7 kg

Design

Certification	CE, TÜV-Bauart, ErP, CU

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of upstream ports	1

Sustainability

European Product Registry for Energy Labelling (EPREL) code	1824494

Logistics data

Harmonized System (HS) code	85285210

Other features

Full HD	✔

4948570122998