

ASUS ProArt -RTX4070S-O12G NVIDIA GeForce RTX 4070 SUPER 12 GB GDDR6X

Brand : ASUS

Product family: ProArt

Product code: 90YV0KC4-M0NA00

Product name : PROART-RTX4070S-O12G



- NVIDIA Studio: RTX and AI-accelerated creator apps, exclusive AI software, and Studio Drivers for unmatched creativity and performance
 - NVIDIA Ada Lovelace Streaming Multiprocessors: Up to 2x performance and power efficiency
 - 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
 - OC Edition: 2565 MHz (OC mode)/ 2535 MHz (Default mode)
 - 3rd Generation RT Cores: Up to 2x ray tracing performance
 - Axial-tech fans scaled up for 21% more airflow
 - 2.5-slot design: allows for greater build compatibility while maintaining premium cooling
 - Dual Ball Fan Bearings last up to twice as long as conventional designs
 - Auto-Extreme precision automated manufacturing for higher reliability
 - GPU Tweak III profile Connect enables creators to seamlessly optimize system performance and cooling for every app
- NVIDIA GeForce RTX 4070 SUPER 12GB GDDR6X, PCI Express 4.0, OpenGL 4.6, 21 Gbps, 192-bit, 750W, 1 x 16-pin, 2.5 Slot

Processor		Performance	
CUDA *	✓	HDCP	✓
CUDA cores	7168	HDCP version	2.3
Graphics processor family *	NVIDIA	Dual Link DVI *	✗
Graphics processor *	GeForce RTX 4070 SUPER	NVIDIA G-SYNC	✓
Processor boost clock speed	2535 MHz	Design	
Processor boost clock speed (OC mode)	2565 MHz	Cooling type *	Active
Maximum resolution *	7680 x 4320 pixels	Cooling technology	ASUS Axial-tech
Parallel processing technology support *	Not supported	Number of fans	3 fan(s)
Maximum displays per videocard	4	Number of slots	2.5
		Product colour	Black
Memory		Power	
Discrete graphics card memory *	12 GB	Minimum system power supply *	750 W
Graphics card memory type *	GDDR6X	Supplementary power connectors	1x 16-pin
Memory bus *	192 bit	System requirements	
Memory bandwidth (max)	21 GB/s	Windows operating systems supported	✓
Ports & interfaces		Weight & dimensions	
Interface type *	PCI Express 4.0	Weight	992 g
HDMI ports quantity *	1	Depth	50 mm
HDMI version	2.1a	Height	120 mm
DisplayPorts quantity *	3	Width	300 mm
DisplayPort version	1.4a	Packaging data	
Performance		Package width	405 mm
OpenGL version *	4.6	Package depth	88.5 mm
Virtual Reality (VR) ready	✓	Package height	233 mm
		Package weight	1.68 kg
		Package type	Box



4711387513170



0197105513181



197105513181

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.