Kingston Technology FURY 128GB 5600MT/s DDR5 ECC Reg CL28 **DIMM (Kit of 4) Renegade Pro EXPO**

Brand: Kingston Technology **Product family: FURY Product code:** KF556R28RBE2K4-128

Product name: 128GB 5600MT/s DDR5 ECC Reg CL28 DIMM (Kit of 4) FURY Renegade Pro EXPO

- Overclocking with ECC
- Increased efficiency
- Intel® XMP 3.0 Certified
- AMD EXPO™ Certified
- Plug N Play**

128GB 5600MT/s DDR5 ECC Reg CL28 DIMM (Kit of 4) FURY Renegade Pro EXPO Kingston Technology FURY 128GB 5600MT/s DDR5 ECC Reg CL28 DIMM (Kit of 4) Renegade Pro EXPO. Component for: PC/Server, Internal memory: 128 GB, Memory layout (modules x size): 4 x 32 GB, Internal memory type: DDR5, Memory clock speed: 5600 MHz, Memory form factor: 288-pin DIMM, CAS latency: 28, ECC, Product colour: Black







| Features | | Operational conditions | | |
|--|-----------------------|----------------------------------|--------------|--|
| Buffered memory type | Registered (buffered) | Storage temperature (T-T) | -55 - 100 °C | |
| On-Die ECC CAS latency Internal memory * Memory layout (modules x size) * Internal memory type * DDR5 | 128 GB | Technical details | | |
| | | Compliance certificates | RoHS | |
| | | Sustainability | | |
| | 4 X 32 GB DDR5 | Sustainability compliance | 1 | |
| Memory clock speed * | 5600 MHz | Sustainability certificates | RoHS | |
| Component for * | PC/Server | Doesn't contain | Halogen | |
| Memory form factor * | 288-pin DIMM | Weight & dimensions | | |
| ECC * | ✓ | Width | 31.2 mm | |
| Memory voltage | 1.25 V | Depth | 133.3 mm | |
| AMD Extended Profiles for Overclocking (EXPO) | ✓ | Height | 3.8 mm | |
| AMD Extended Profiles for Overclocking (EXPO) version | 1.1 | Weight | 76.67 g | |
| SPD profile | | Packaging data | | |
| Country of origin | China, Taiwan | Package width | 104.1 mm | |
| Product colour | Black | Package depth | 167.6 mm | |
| Cooling type | Heatsink | Package height | 35.6 mm | |
| Lead plating | Gold | Package weight | 109.34 g | |
| JEDEC standard | ✓ | Logistics data | | |
| Operational conditions | | Master (outer) case width | 207 mm | |
| Operating temperature (T-T) | 0 - 95 °C | Master (outer) case length | 469.9 mm | |
| | | Master (outer) case height | 105.4 mm | |
| | | Master (outer) case gross weight | 1.45 kg | |
| | | Products per master (outer) case | 10 pc(s) | |





740617342161

0740617342161

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.