

## DELL P Series P2425H\_WOST computer monitor 61 cm (24") 1920 x 1080 pixels Full HD LCD Black

**Brand :** DELL **Product family:** P Series **Product code:** DELL-P2425HWO

Product name: P2425H\_WOST

- 61.0cm (24") Full HD 1920 x 1080 LED IPS
- 8ms, 16:9, 250cd/m<sup>2</sup>, 1500:1
- USB, VGA, HDMI, DisplayPort

61.0cm (24") Full HD 1920 x 1080 LED IPS, 16:9, 250cd/m², 16.7M, 8ms, 178°/178°, 1500:1

## DELL P Series P2425H\_WOST computer monitor 61 cm (24") 1920 x 1080 pixels Full HD LCD Black:

Stay productive. Get enhanced visual comfort and seamless connectivity with this FHD monitor (without stand), certified by TÜV for 4-star eye comfort.

DELL P Series P2425H\_WOST. Display diagonal: 61 cm (24"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black







Display		Ports & interfaces	
Display diagonal * Display resolution * HD type *	61 cm (24") 1920 x 1080 pixels Full HD	HDCP HDCP version AC (power) in	✓ 1.4 ✓
Native aspect ratio * Display technology * Panel type * LED backlight Backlight type Touchscreen * Display brightness (typical) Response time Anti-glare screen Screen shape * Supported graphics resolutions	16:9 LCD IPS  LED  X 250 cd/m² 8 ms  Flat 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024	Ergonomics  VESA mounting * Panel mounting interface Cable management Cable lock slot * Cable lock slot type Height adjustment * Pivot Swivelling Tilt adjustment On Screen Display (OSD) Plug and Play	V 100 x 100 mm V Kensington X X X
Supported video modes Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal	(SXGA), 1280 x 720 (HD 720), 1600 x 900, 1920 x 1080 (HD 1080)  480p, 576p, 720p, 1080p  1500:1  100 Hz  178°  16.7 million colours  5 ms  0.2745 x 0.2745 mm  92.53 ppi  30 - 110 kHz  48 - 100 Hz  52.7 cm	LED indicators  Power  Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current	C Not available 12 kWh 11.7 W 0.3 W 65 W 0.3 W 100 - 240 V 50/60 Hz 1.5 A

Display         Power         Prover supply type         Internal           Viewable size, vertical         29.6 cm         Power supply type         At a G           Surface hardness         3H         Derational conditions           Surface hardness         3H         Operating temperature (T-T)         -20-60 °C           Dell Comfort/Wew technology         √         Operating temperature (T-T)         -20-60 °C           Performance         √         Operating temperature (T-T)         -20-60 °C           NVIDIA G-SYNC*         X         Storage relative humidity (H-H)         10 -80%           NVIDIA G-SYNC*         X         Operating altitude         5 -90%           AND FreeSync*         X         Operating altitude         0 -12192 m           Low Blue Light technology         √         Non-operating altitude         0 -2192 m           Low Blue Light technology         √         Stand included         X           Windows sperating systems         MacOS         Cables included         X           Multicating systems         MacOS         Cables included         X           Multicansers         X         Black         ACD DisplayPort cable length         1.8 m           Bulltin in speaker(s)*         Black         Dept with without st				
Viewable size diagonal         60.5 cm         Energy efficiency scale         At 60           Surface hardness         3H         Operational conditions           SKGB coverage (typical)         99%         Operating temperature (T-T)         2-0 ± 0° C           Performance         Operating relative humidity (H+H)         10 ± 80%           NVIDIA G-SYNC*         X         Storage relative humidity (H+H)         5 ± 90%           AMD FreeSync*         X         Operating altitude         0 ± 5000 m           Flicker-free technology         √         Non-operating altitude         0 ± 1219 zm           Low Blue Light technology         √         Cables included         X           Windows operating systems         Windows 10, Yes         Stand included         X           Windows operating systems supported         MacO         Cables included         X           Multimedia         X         AC DisplayPort, HDMI, USB Type-A           Built-in speaker(s)*         X         Bull Modable length         1.8 m           Built-in speaker(s)*         X         Bull Modable length         1.8 m           Product color*         Black         Depth (without stand)         314.2 mm           Product color*         Black         Berel width (without stand)         312.2	Display		Power	
Surface hardness         3H         Operational conditions           sRGB coverage (typical)         99%         Operating temperature (T-T)         0 - 40 °C           Dell Comfort/View technology         √         Storage temperature (T-T)         2-20 - 60 °C           Performance         ✓         Operating relative humidity (H-H)         5 - 90%           NVIDIA G-SYNC*         X         Storage relative humidity (H-H)         5 - 90%           AMD FreeSync*         X         Operating altitude         0 - 5000 om           Flicker-free technology         ✓         Packaging content           Uow Blue Light technology         ✓         Packaging content           Windows operating systems         Windows 10, Yes         Stand included         X           Mac operating systems supported         MacOS         Cables included         XC         DisplayPort, HDMI, USB Type-A           Multi-in speaker(s)*         X         HDMI cable length         1.8 m         Bult-in speaker(s)*         X         Bult-in user and	Viewable size, vertical	29.6 cm	Power supply type	Internal
SRGB coverage (typical)         99%         Operating temperature (T-T)         0.40 °C           Deil Comfort/View technology         7         Operating temperature (T-T)         -20 - 60 °C           Performance         Verating relative humidity (H-H)         10 - 80%           NVIDIA G-SYNC*         X         Storage relative humidity (H-H)         5 - 90%           AMD FreeSync*         X         Operating altitude         0 - 5000 m           Flicker-free technology         4         Non-operating altitude         0 - 5000 m           Low Blue Light technology         4         Packaging content           Windows operating systems         Windows 10, Yes         Stadi included         X           Multimedia         Windows 10, Yes         Stadi included         AC, DisplayPort, HDMI, USB Type-A           Multimedia         Yes         AC, DisplayPort, HDMI, USB Type-A           Built-in speaker(s)*         X         Built-in speaker(s)*         AC, DisplayPort, HDMI, USB Type-A           Built-in camera         X         Width (without stand)         1.8 m           Built-in camera         Black         Depth (without stand)         53.6 mm           Product colour         Black         Depth (without stand)         31.2 kg           Built-in USB hub **         Yes	Viewable size diagonal	60.5 cm	Energy efficiency scale	A to G
Dell ComfortView technology         ✓ Operating temperature (T-T)         2-0 - 60 °C           Performance         Operating relative humidity (H-H)         10 - 80%           NVIDIA G-SYNC*         X         Storage relative humidity (H-H)         5 - 90%           AMD FreeSync*         X         Operating altitude         0 - 5000 m           Elicker-free technology         ✓         Operating altitude         0 - 5000 m           Low Blue Light technology         ✓         Packaging content           Windows operating systems         Windows 10, Yes         Stand included         X           Windows operating systems supported         Mac OS         Cables included         XC         DisplayPort, AIDMI, USB Type-A           Multimedia         X         HDMI cable length         1.8 m         Built-in speaker(s)*         ME         ME         ME           Built-in speaker(s)*         X         HDMI cable length         1.8 m         ME         ME         MI         ME         ME         ME         ME         ME         ME         ME         ME         ME         MI         MI         ME         M			Operational conditions	
Storage temperature (T-T)         -20-60 °C           Performance         Storage relative humidity (H-H)         10 - 80%           NVIDIA G-SYNC °         X         Storage relative humidity (H-H)         5 - 90%           AMD FreeSync °         X         Operating altitude         0 - 5000 m           Flicker-free technology         √         Non-operating altitude         0 - 12192 m           Low Blue Light technology         √         Packaging content           Windows operating systems         Windows 10, Yes         Stand included         X           Mac operating systems supported         MacOS         Cables included         AC, DisplayPort, HDMI, USB Type-A           Multimedia         X         Use start guide         √           Built-in speaker(s) *         X         HDMI cable length         1.8 m           Built-in speaker(s) *         X         HDMI cable length         1.8 m           Built-in camera *         X         Width (without stand)         538.6 mm           Product colour *         Black         Depth (without stand)         50 mm           Front bezel colour         Black         Pecke width (side)         3.12 kg           Built-in USB hub **         ✓         Sezel width (bottom)         1.2 cm	5		Operating temperature (T-T)	0 - 40 °C
NVIDIA G-SYNC* X Storage relative humidity (H-H) 5 - 90% AMD FreeSync* X Operating altitude 0 - 5000 m Flicker-free technology	Dell ComfortView technology	✓	Storage temperature (T-T)	-20 - 60 °C
AMD FreeSync* X Operating altitude 0 - 5000 m Flicker-free technology	Performance		Operating relative humidity (H-H)	10 - 80%
Flicker-free technology  Low Blue Light technology  Windows operating systems supported  Mac operating systems supported  Mac operating systems supported  Mac operating systems supported  Mac operating systems supported  MacOS  Cables included  Ac, DisplayPort, HDMI, USB Type-A  Quick start guide  OpisplayPort cable length  1.8 m  HDMI cable length  1.8	NVIDIA G-SYNC *	×	Storage relative humidity (H-H)	5 - 90%
Low Blue Light Echnology       Very Mindows 10, Yes       Packaging content         Windows operating systems supported       Windows 10, Yes       Stand included       X         Mac operating systems supported       MacOS       Cables included       AC, DisplayPort, HDMI, USB Type-A         Multimedia       VisipalyPort cable length       1.8 m         Built-in speaker(s)*       X       HDMI cable length       1.8 m         Built-in camera*       X       Weight & dimensions         Weight & dimensions         Postag       Black       Depth (without stand)       50 mm         Front bezel colour       Black       Depth (without stand)       314.2 mm         Ports & interfaces       Weight without stand)       312.2 kg         Built-in USB hub*       ✓       Bezel width (side)       3.12 kg         USB hub version       3.2 Gen 1 (3.1 Gen 1)       Bezel width (top)       5.8 mm         USB Type-A downstream ports quantity       1       Packaging data         USB Type-A downstream ports quantity       1       Sachage weight       5.34 kg         USB Type-C downstream ports quantity       1       Sustainability compliance       ✓         USB Power Delivery up to       15 W       Sustainability certificates       TÜV mark	AMD FreeSync *	×	Operating altitude	0 - 5000 m
Windows operating systems supported MacOS Cables included AC, DisplayPort, HDMI, USB Type-A Mac operating systems supported MacOS Cables included AC, DisplayPort, HDMI, USB Type-A Mac operating systems supported MacOS Quick start guide VisplayPort cable length 1.8 m Quick start guide 1.8 m Built-in speaker(s)* X Weight & dimensions  Built-in speaker(s)* X Weight & dimensions  Product camera* X Weight & dimensions  Product colour * Black Depth (without stand) 50 mm  Front bezel colour Black Height (without stand) 50 mm  Front bezel colour Black Height (without stand) 314.2 mm  Ports & interfaces Weight (without stand) 314.2 mm  Ports & interfaces Built-in USB hub * Veight (without stand) 31.2 kg  Built-in USB hub * Sezel width (side) 5.8 mm  USB hub version Bezel width (top) 5.8 mm  USB hub version Ports quantity Bezel width (top) 1.2 cm  Ports Quantity Packaging data  USB Type-A downstream ports quantity Speech Quantity Sustainability compliance Sustainability compliance VID Mark  VSB Power Delivery up to 15 W Sustainability certificates TÜV mark  VSB Power Delivery up to 15 W Sustainability certificates TÜV mark  USB Power Delivery Up to 14 Compatibility Poors (Mercury, PVC/BFR)  HDMI version 1.4 Compatibility Compatibility Compatibility Compatibility Version LA Compatibility Compatibility Compatibility Version LA Compatibility Compatibility Compatibility Version LA Compatibility Compatibility Version LA Compatibility Compatibility Compatibility Version LA Compatibility Compatibility Version LA Compatibility Compatibility Version LA Compatibili	Flicker-free technology	✓	Non-operating altitude	0 - 12192 m
supported       Windows 10, Yes       Stand included       XCD isplayPort, HDMI, USB Type-A         Multimedia       Voick start guide       Voick start guide <td>· · · · · · · · · · · · · · · · · · ·</td> <td>✓</td> <td>Packaging content</td> <td></td>	· · · · · · · · · · · · · · · · · · ·	✓	Packaging content	
Mac operating systems supported     MacOS     Cables included     AC, DisplayPort, HDMI, USB Type-A       Multimedia     Quick start guide     V       Built-in speaker(s)*     X     HDMI cable length     1.8 m       Built-in camera*     X     HDMI cable length     1.8 m       Weight & dimensions       Weight & dimensions       Weight & dimensions       Ports of interfaces     Black     Depth (without stand)     50 mm       Ports & interfaces     Weight (without stand)     3.12 kg       Built-in USB hub*     V     Bezel width (top)     3.12 kg       Built-in USB hub *     V     Bezel width (top)     5.8 mm       USB Type-B upstream ports quantity     3.2 Gen 1 (3.1 Gen 1)     Bezel width (bottom)     1.2 cm       Wish colspan="3">Porkaging data       USB Type-A downstream ports quantity     3     Package weight     5.34 kg       USB rype-C downstream ports quantity     Sustainability     1.8 m       USB Power Delivery     V     Sustainability       USB Power Delivery up to     15 W     Sustainability compliance     V       VSB Power Delivery up to     15 W     Sustainability compliance     V				



5397184821718

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.