

LG 55VH7J-H Signage Display Panorama design 139.7 cm (55") 700 cd/m² Full HD Black 24/7

Brand : LG

Product code: 55VH7J-H

Product name : 55VH7J-H

- Brightness(Typ.) : 700 nit

- Bezel : 1.74mm (Panel Bezel to Panel Bezel), 1.3mm (T/L), 0.44mm (B/R)

- Depth : 86.9 mm

- Interface : HDMI/ DP/ DVI-D/ USB/ RS232C/ RJ45/ Audio/ IR

55", 700 nits, 1920 x 1080 px, FHD, IPS, 100-240V, 50/60Hz, 1212.2 x 683.0 x 86.9 mm, 18.8 kg LG 55VH7J-H. Product design: Panorama design. Display diagonal: 139.7 cm (55"), Display resolution: 1920 x 1080 pixels, Display brightness: 700 cd/m², HD type: Full HD. Operating hours (hours/days): 24/7. Product colour: Black







Display		Design	
Panel type LED backlighting type	IPS Direct-LED	VESA mounting * Panel mounting interface	✔ 600 x 400 mm
Display diagonal * Display resolution * Display brightness * HD type * Touchscreen * Native aspect ratio Response time Contrast ratio (typical) Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical Display number of colours Rated lifetime Native refresh rate	139.7 cm (55") 1920 x 1080 pixels 700 cd/m ² Full HD × 16:9 8 ms 1000:1 500000:1 178° 178° 1.07 billion colours 60000 h 60 Hz	PerformancePurpose *On Screen Display (OSD)Operating hours (hours/days)PowerPower consumption (typical) *Power consumption (off)Energy efficiency class (SDR)Energy consumption (SDR) per 1000hoursAC input voltageAC input frequencyEnergy efficiency scale	Commercial 24/7 250 W 0.5 W G 157 kWh 100-240 V 50/6 Hz A to G
Haze rate	28%	Weight & dimensions	
Ports & interfaces HDMI ports quantity * 2 HDMI version 2.2 DVI port * ✓	Display width Display depth Display height Display weight	1212.2 mm 86.9 mm 683 mm 18.8 kg	
DVI-D ports quantity	1	Packaging data	5
DisplayPorts quantity *1USB port *IUSB ports quantity1USB version2.0	✓ 1 2.0	Package width Package depth Package height Package weight	1353 mm 263 mm 855 mm 31 kg
Ethernet LAN * Ethernet LAN (RJ-45) ports	✓ 1	Packaging content	
RS-232C	1	Remote control included Cables included	✓ DisplayPort, Power, RS-232
Design Product design *	Panorama design	Operational conditions	
Product colour *	Black	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%





8806091407658

0195174014035



195174014035

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.