iiyama

iiyama ProLite XUB2794QSU-B6 computer monitor 68.6 cm (27") 2560 x 1440 pixels Wide Quad HD LCD Black

Brand : iiyama

Product family: ProLite

Product code: XUB2794QSU-B6

Product name : XUB2794QSU-B6

- 3-side borderless
- VA matrix, matte finish
- HDMI x1, DisplayPort x1
- USB HUB x2 (3.2 Gen 1 (5Gbps, DC5V, 900mA))

PROLITE XUB2794QSU-B6 - 27" WQHD VA panel with 100Hz refresh rate and 150mm height adjustable stand

iiyama ProLite XUB2794QSU-B6. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Wide Quad HD, Display technology: LCD, Response time: 1 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

Display

Display diagonal *	68.6 cm (27")
Display resolution *	2560 x 1440 pixels
HD type *	Wide Quad HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	VA
Touchscreen *	✖
Display brightness (typical)	250 cd/m²
Response time	1 ms
Screen shape *	Flat
Contrast ratio (typical) *	4000:1
Contrast ratio (dynamic)	80000000:1
Maximum refresh rate *	100 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.233 x 0.233 mm
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.5 cm
DDC/CI	✓
sRGB coverage (typical)	96%
NTSC coverage (typical)	72%

Performance

NVIDIA G-SYNC *	✖
AMD FreeSync *	✓
AMD FreeSync type	FreeSync
Flicker-free technology	✓
Low Blue Light technology	✓

Multimedia

Built-in speaker(s) *	✓
Built-in camera *	✖
Number of speakers	2
RMS rated power	4 W

Design

Market positioning *	Office
Product colour *	Black

Ports & interfaces

HDCP	✓

Ergonomics

VESA mounting *	✓
Panel mounting interface	100 x 100 mm
Cable management	✓
Cable lock slot *	✓
Cable lock slot type	Kensington
Height adjustment *	✓
Height adjustment	15 cm
Pivot	✓
Pivot angle	0 - 90°
Swivelling	✓
Swivel angle range	-180 - 180°
Tilt angle range	23 - 5°
On Screen Display (OSD)	✓
On Screen Display (OSD) languages	Czech, German, Dutch, English, Spanish, French, Italian, Japanese, Polish, Russian
Number of OSD languages	10

Power

Energy efficiency class (SDR) *	F
Energy consumption (SDR) per 1000 hours *	26 kWh
Power consumption (typical) *	24 W
Power consumption (standby) *	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G

Packaging content

Cables included	AC, DisplayPort, HDMI, USB
Quick start guide	✓

Weight & dimensions

Width (with stand)	613.5 mm
Depth (with stand)	209.5 mm
Height (with stand)	551 mm
Weight (with stand)	5.3 kg

Design

Certification	TCO Certified, CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS, ErP, WEEE, REACH, UKCA

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
HDMI *	✔
HDMI ports quantity	1
DisplayPorts quantity	1
Headphone out *	✔

Packaging data

Package width	691 mm
Package depth	447 mm
Package height	142 mm
Package weight	6.6 kg
Package type	Box

Sustainability

European Product Registry for Energy Labelling (EPREL) code	1605619

4948570122707