

## ASUS Dual -RTX4070S-12G NVIDIA GeForce RTX 4070 SUPER 12 GB GDDR6X

**Brand :** ASUS

**Product family:** Dual

**Product code:** 90YV0K83-M0NA00

**Product name :** DUAL-RTX4070S-12G



- Powered by NVIDIA DLSS3, ultra-efficient Ada Lovelace arch, and full ray tracing
  - 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
  - 3rd Generation RT Cores: Up to 2x ray tracing performance
  - Axial-tech fan design features a smaller fan hub that facilitates longer blades and a barrier ring that increases downward air pressure
  - A 2.56-slot design maximizes compatibility and cooling efficiency for superior performance in small chassis
  - 0dB technology lets you enjoy light gaming in relative silence
  - Dual ball fan bearings can last up to twice as long as sleeve bearing designs
  - Auto-Extreme precision automated manufacturing for higher reliability
- NVIDIA GeForce RTX 4070 SUPER 12GB GDDR6X, PCI Express 4.0, 21 Gbps, 192-bit, 750W, 2.56 Slot, 1 x 16-pin

[ASUS Dual -RTX4070S-12G NVIDIA GeForce RTX 4070 SUPER 12 GB GDDR6X:](#)

ASUS Dual GeForce RTX™ 4070 SUPER 12GB GDDR6X with two powerful Axial-tech fans and a 2.56-slot design for broad compatibility

<b>Processor</b>		<b>Ports &amp; interfaces</b>	
CUDA *	✓	DisplayPort version	1.4a
CUDA cores	7168	<b>Performance</b>	
Graphics processor family *	NVIDIA	OpenGL version *	4.6
Graphics processor *	GeForce RTX 4070 SUPER	HDCP	✓
Processor boost clock speed	2475 MHz	HDCP version	2.3
Processor boost clock speed (OC mode)	2505 MHz	Dual Link DVI *	✗
Maximum resolution *	7680 x 4320 pixels	NVIDIA G-SYNC	✓
Parallel processing technology support *	Not supported	<b>Design</b>	
Maximum displays per videocard	4	Cooling type *	Active
<b>Memory</b>		Cooling technology	ASUS Axial-tech
Discrete graphics card memory *	12 GB	Number of fans	2 fan(s)
Graphics card memory type *	GDDR6X	Form factor	Full-Height/Full-Length (FH/FL)
Memory bus *	192 bit	Number of slots	2.56
Memory bandwidth (max)	21 GB/s	Product colour	Multicolour
<b>Ports &amp; interfaces</b>		<b>Power</b>	
Interface type *	PCI Express 4.0	Minimum system power supply *	750 W
HDMI ports quantity *	1	Supplementary power connectors	1x 16-pin
HDMI version	2.1a	<b>Weight &amp; dimensions</b>	
DisplayPorts quantity *	3	Depth	51.1 mm
		Height	133.9 mm
		Width	267 mm
		<b>Packaging data</b>	
		Package type	Box



4711387442975



0197105442986



197105442986

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.