



D-Link DGS-1210-08P network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Brand : D-Link

Product code: DGS-1210-08P

Product name : DGS-1210-08P

DGS-1210-08P: 8-Port, Gigabit, PoE, Smart Switch with 2 SFP ports (8 x PoE ports, fanless)
D-Link DGS-1210-08P. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 16000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3af. Power over Ethernet (PoE). Rack mounting



| Management features | | Technical details | |
|---|---|--|-------------|
| Switch type * | Managed | Shipping (inner) case length | 38.2 cm |
| Switch layer | L2 | Shipping (inner) case net weight | 10.8 kg |
| Quality of Service (QoS) support | ✓ | Products per shipping (inner) case | 5 pc(s) |
| MIB support | 1213 MIB II, 1493 Bridge MIB, 1907 SNMP v2 MIB, 1215 Trap Convention MIB, 2233 Interface Group MIB, D-Link Private MIB, Power-Ethernet MIB, LLDP MIB, D-Link ZoneDefense MIB1 | Pallet gross weight (air) | 436.1 kg |
| | | Master (outer) cases per pallet (air) | 36 pc(s) |
| | | Products per pallet (air) | 180 pc(s) |
| | | Pallet gross length | 110 cm |
| | | Pallet gross width | 120 cm |
| | | Pallet height (air) | 140.3 cm |
| | | Pallet gross weight (sea) | 644.9 kg |
| | | Master (outer) cases per pallet (sea) | 54 pc(s) |
| | | Products per pallet (sea) | 270 pc(s) |
| | | Pallet height (sea) | 2.04 m |
| | | Shipping (inner) case gross weight | 11.6 kg |
| Ports & interfaces | | Power | |
| Basic switching RJ-45 Ethernet ports quantity * | 8 | AC input voltage | 100 - 240 V |
| Basic switching RJ-45 Ethernet ports type * | Gigabit Ethernet (10/100/1000) | AC input frequency | 50 - 60 Hz |
| SFP module slots quantity | 2 | Power over Ethernet (PoE) | |
| Network | | Power over Ethernet (PoE) * | ✓ |
| Networking standards * | IEEE 802.1D, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3af | Power over Ethernet plus (PoE+) ports quantity | 8 |
| 10G support * | ✓ | Operational conditions | |
| Full duplex | ✓ | Operating temperature (T-T) | -5 - 50 °C |
| Flow control support | ✓ | Storage temperature (T-T) | -20 - 70 °C |
| Spanning tree protocol | ✓ | Operating relative humidity (H-H) | 0 - 95% |
| Head-of-line (HOL) blocking | ✓ | Storage relative humidity (H-H) | 0 - 95% |
| VLAN support | ✓ | Weight & dimensions | |
| Data transmission | | Width | 280 mm |
| Switching capacity * | 20 Gbit/s | Depth | 180 mm |
| MAC address table * | 16000 entries | Height | 44 mm |
| Jumbo frames support | ✓ | Packaging data | |
| Packet buffer memory | 6 MB | Package width | 288 mm |
| Security | | Package depth | 331 mm |
| DHCP features | DHCP server, DHCP client | Package height | 72 mm |
| Access Control List (ACL) | ✓ | Package weight | 2.17 kg |
| IGMP snooping | ✓ | Logistics data | |
| MAC address filtering | ✓ | Harmonized System (HS) code | 85176990 |
| Static port security | ✓ | Other features | |
| SSH/SSL support | ✓ | Packet transfer speed | 14.9 Mp/s |
| Multicast features | | Power LED | ✓ |
| Multicast support | ✓ | | |
| Protocols | | | |
| Management protocols | SNMP, RMON | | |
| Data link protocols | IP | | |

Design

| | |
|------------------|------------|
| Rack mounting * | ✓ |
| Stackable * | ✓ |
| Product colour | Black |
| LED indicators | ✓ |
| Cable management | ✓ |
| Safety | cUL, LVD |
| Certification | CE Class A |

Technical details

| | |
|------------------------------|---------|
| Shipping (inner) case height | 31.7 cm |
| Shipping (inner) case width | 34.6 cm |



0790069391958



790069391958

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.