



Fujitsu Smart-UPS uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1200 W 8 AC outlet(s)

Brand : Fujitsu

Product code: FJX1500RM2UNC

Product name : Smart-UPS



Smart-UPS X 1500VA Rack/Tower LCD 230V with Network Card

Fujitsu Smart-UPS uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1200 W 8 AC outlet(s):

Fujitsu UPS devices ensure high-performance power supply protection for systems and data, and thus provide reliable protection against power failure, current fluctuations and electrical interference. Fujitsu offers both line interactive (VI) and online (VFI) devices with double conversion technology in line with the UPS classification according to IEC 62040-3. Capacities of up to 3000VA provide the right power supply and technology for all individual requirements.

The use of uninterruptible power supplies can particularly benefit your company from a financial viewpoint: Having to search for and restore lost or damaged data after a power failure can cost a great deal of time and money. In such incidents UPS helps to protect your data.



Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	3 h
Output power capacity *	1.5 kVA	Hot-swap battery	✓
Output power *	1200 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	151 V	Design	
Input operation voltage (max) *	302 V	Form factor *	Rackmount
Input frequency *	50/60 Hz	Rack capacity	2U
Output frequency regulation	50/60 Hz	Cable length	1.83 m
Automatic Voltage Regulation (AVR)	✓	Product colour *	Black
Surge energy rating	645 J	Display type	LCD
Efficiency	98.5%	LED indicators	✓
Emergency Power Off (EPO)	✓	Operational conditions	
Noise level	40 dB	Operating temperature (T-T)	0 - 40 °C
Surge protection	✓	Storage temperature (T-T)	-15 - 45 °C
Audible alarm(s)	✓	Operating relative humidity (H-H)	0 - 95%
Audible alarm modes	Low battery alarm, Overload alarm	Storage relative humidity (H-H)	0 - 95%
Auto-restart	✓	Operating altitude	0 - 3000 m
Ports & interfaces		Non-operating altitude	0 - 15000 m
AC outlet types	C13 coupler	Technical details	
Power plug	C14 coupler	Sustainability certificates	RoHS
AC outlets quantity	8 AC outlet(s)	Weight & dimensions	
Number of output IEC jumpers	2	Width	432 mm
USB port	✓	Depth	490 mm
SmartSlot	✓	Height	89 mm
Battery		Weight	24.8 kg
Battery technology	Sealed Lead Acid (VRLA)	Package width	589 mm
Typical backup time at full load	5.8 min	Package depth	620 mm
Typical backup time at half load	17.2 min	Package height	246 mm
Battery life (max)	5 year(s)	Package weight	30 kg

Packaging data

Rack mount kit	✓
Cables included	RS-232, USB cable
Quick installation guide	✓



5712505309926

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-JUN-2024. Prints or copies of Information are only valid on the printed Publication date