



## EIZO FlexScan EV2795-WT LED display 68.6 cm (27") 2560 x 1440 pixels Quad HD White

**Brand :** EIZO

**Product family:** FlexScan

**Product code:** EV2795-WT

**Product name :** EV2795-WT

27" IPS, QHD 2560 x 1440 px, 350 cd/m<sup>2</sup>, 5 ms, 16:9, USB-C, LAN, DP, HDMI, 16 kWh/1000h, D  
EIZO FlexScan EV2795-WT. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: White



Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	HDCP	✓
Display resolution *	2560 x 1440 pixels	<b>Network</b>	
HD type *	Quad HD	Ethernet LAN	✓
Native aspect ratio *	16:9	<b>Ergonomics</b>	
Display technology *	LED	VESA mounting *	✓
Panel type *	IPS	Panel mounting interface	100 x 100 mm
Backlight type	LED	Cable lock slot *	✓
Touchscreen *	✗	Cable lock slot type	Kensington
Display brightness (typical)	350 cd/m <sup>2</sup>	Height adjustment *	✓
Response time	5 ms	Height adjustment	17.7 cm
Screen shape *	Flat	Pivot	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1440	Pivot angle	-90 - 90°
		Swivelling	✓
		Swivel angle range	0 - 344°
		Tilt adjustment	✓
		Tilt angle range	-5 - 35°
Contrast ratio (typical) *	1000:1	On Screen Display (OSD)	✓
Maximum refresh rate *	60 Hz	On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Swedish
Viewing angle, horizontal	178°	<b>Power</b>	
Viewing angle, vertical	178°	Energy efficiency class (SDR) *	D
Display number of colours *	16.78 million colours	Energy consumption (SDR) per 1000 hours *	16 kWh
Pixel pitch	0.233 x 0.233 mm	Power consumption (typical) *	16.1 W
Pixel density	109 ppi	Power consumption (standby) *	0.5 W
Viewable size, horizontal	59.7 cm	AC input voltage	100 - 240 V
Viewable size, vertical	33.6 cm	AC input frequency	50 - 60 Hz
Viewable size diagonal	68.5 cm	Energy efficiency scale	A to G
Digital horizontal frequency	31 - 89 kHz		
Digital vertical frequency	59 - 61 Hz		
Colour gamut standard	sRGB		

<b>Performance</b>		<b>Operational conditions</b>	
Flicker-free technology	✓	Operating temperature (T-T)	5 - 35 °C
Low Blue Light technology	✓	Storage temperature (T-T)	-20 - 60 °C
<b>Multimedia</b>		Operating relative humidity (H-H)	20 - 80%
Built-in speaker(s) *	✓	Storage relative humidity (H-H)	10 - 90%
Number of speakers	2	<b>Packaging content</b>	
RMS rated power	2 W	Stand included	✓
<b>Design</b>		Cables included	AC, USB Type-C to USB Type-C
Market positioning *	Business	Quick start guide	✓
Product colour *	White	<b>Weight &amp; dimensions</b>	
	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC	Width (with stand)	611 mm
Certification		Depth (with stand)	230 mm
		Height (with stand)	369 mm
		Weight (with stand)	8.5 kg
		Width (without stand)	611 mm
		Depth (without stand)	56 mm
		Height (without stand)	357 mm
		Weight (without stand)	5.7 kg
<b>Ports &amp; interfaces</b>		<b>Sustainability</b>	
Built-in USB hub *	✓	Sustainability compliance	✓
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Sustainability certificates	ENERGY STAR, EPEAT Climate +, EPEAT Gold, TCO
Number of upstream ports	1	European Product Registry for Energy Labelling (EPREL) code	356881
USB Type-A downstream ports quantity	3	<b>Logistics data</b>	
USB Type-C downstream ports quantity	1	Harmonized System (HS) code	85285210
USB Type-C DisplayPort Alternate Mode	✓	<b>Other features</b>	
DVI port	✗	Ethernet LAN data rates	10,100,1000 Mbit/s
HDMI *	✓	Ethernet LAN (RJ-45) ports	1
HDMI ports quantity	1		
DisplayPorts quantity	1		
Audio input	✓		
Headphone out *	✓		
Headphone outputs	1		
Headphone connectivity	3.5 mm		



4995047056645

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.