## Platinet EV Charging Type2 Cable, Cable 5m, Charging Speed 11kW, Single or Three Phase power supply (16A), Type 2 to Type 2 connectors (current and most popular standard), Suitable for all electric vehicle manufacturers, Connector White/Black Cable



## Brand : Platinet

Product code: PEVC11KW5B

**Product name :** EV Charging Type2 Cable, Cable 5m, Charging Speed 11kW, Single or Three Phase power supply (16A), Type 2 to Type 2 connectors (current and most popular standard), Suitable for all electric vehicle manufacturers, Connector White/Black Cable

EV Charging Type2 Cable, 11kW, Cable 5m, Single or Three Phase power supply, Connector White/Black Cable

Platinet EV Charging Type2 Cable, Cable 5m, Charging Speed 11kW, Single or Three Phase power supply (16A), Type 2 to Type 2 connectors (current and most popular standard), Suitable for all electric vehicle manufacturers, Connector White/Black Cable:

Electric Vehicle Charging Cable Simple and convenient operation. Stronger and more durable. Convenient storage Charging with ""NO-LIMITS" We can safely take the PLATINET.

We can safely take the PLATINET Type 2 cable for charging electric cars on a trip throughout Europe. Becasue of the universal Type 2 plugs, they are compatible with all stations that support this type of charging. It allows you to charge electric cars with a power of up to 11kW. It is terminated with Type 2 connectors, which are operated at charging stations all over Europe. Its low weight makes it easy to use, and the cable itself will not take up much space in the trunk of our vehicle.

Features		Power	
Cable colour *BlackHandle colourBlack, WhiteConnector 1 *Type 2Connector 2 *Type 2Connector 1 form factorAngledConnector 2 form factorAngledInternational Protection (IP) codeIP54Protective cap✓	Black, White Type 2	Maximum operating power (three- phase) Maximum operating current (three- phase) Operating voltage	11 kW 16 A 480 V
	Angled IP54	Weight & dimensions   Cable length *   Cable diameter	5 m 1.35 cm
Power		Operational conditions	
Number of phases *	3	Operating temperature (T-T)	-35 - 50 °C
		Packaging data	
		Carrying case	✓

Quantity per pack \*

1 pc(s)

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.