

ASUS ProArt -RTX4060TI-O16G NVIDIA GeForce RTX 4060 Ti 16 GB GDDR6

Brand : ASUS

Product family: ProArt

Product code: 90YV0JH2-M0NA00

Product name : PROART-RTX4060TI-O16G



- NVIDIA Ada Lovelace Streaming Multiprocessors: Up to 2x performance and power efficiency
- 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
- 3rd Generation RT Cores: Up to 2x ray tracing performance
- OC edition: 2685 MHz (OC mode)/ 2655 MHz (Default mode)
- Axial-tech fans scaled up for 21% more airflow
- 2.5-slot design: allows for greater build compatibility while maintaining premium cooling
- Dual ball fan bearings last up to twice as long as conventional designs
- 0dB technology lets you enjoy light gaming in relative silence
- Auto-Extreme precision automated manufacturing for higher reliability
- GPU Tweak III profile Connect enables creators to seamlessly optimize system performance and cooling for every app

ProArt GeForce RTX 4060 Ti OC Edition 16GB GDDR6 Gaming Graphics Card (NVIDIA GeForce RTX4060Ti DLSS 3, PCIe 4.0, 1x HDMI 2.1a, 3x DisplayPort 1.4a, PROART-RTX4060TI-O16G)

Processor		Performance	
CUDA *	✓	OpenGL version *	4.6
CUDA cores	4352	HDCP	✓
Graphics processor family *	NVIDIA	HDCP version	2.3
Graphics processor *	GeForce RTX 4060 Ti	Dual Link DVI *	✗
Processor boost clock speed	2655 MHz	NVIDIA G-SYNC	✓
Processor frequency (OC mode)	2685 MHz	NVIDIA Ansel	✓
Maximum resolution *	7680 x 4320 pixels	Design	
Parallel processing technology support *	Not supported	Cooling type *	Active
Maximum displays per videocard	4	Cooling technology	ASUS Axial-tech
Memory		Number of fans	3 fan(s)
Discrete graphics card memory *	16 GB	Form factor	Full-Height/Full-Length (FH/FL)
Graphics card memory type *	GDDR6	Number of slots	2.5
Memory bus *	128 bit	Product colour	Black
Memory bandwidth (max)	18 GB/s	Power	
Ports & interfaces		Minimum system power supply *	650 W
Interface type *	PCI Express 4.0	Supplementary power connectors	1x 8-pin
HDMI ports quantity *	1	Weight & dimensions	
HDMI version	2.1a	Weight	960 g
DisplayPorts quantity *	3	Depth	300 mm
DisplayPort version	1.4a	Height	50 mm
Performance		Width	120 mm
TV tuner integrated *	✗	Packaging data	
DirectX version *	12 Ultimate	Package width	405 mm
		Package depth	233 mm
		Package height	88.5 mm
		Package weight	1.62 kg
		Package type	Box



4711387275504



0197105285255



197105285255

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.