



i-tec USB-C Metal Ergonomic 3x 4K Display Docking Station with Power Delivery 100 W + Universal Charger 100 W

Brand : i-tec

Product code:
C31FLAT2PDPRO100WUK

Product name : USB-C Metal Ergonomic 3x 4K Display Docking Station with Power Delivery 100 W + i-tec Universal Charger 100 W



USB-C Metal Ergonomic 3x 4K Display Docking Station with Power Delivery 100 W + i-tec Universal Charger 100 W

i-tec USB-C Metal Ergonomic 3x 4K Display Docking Station with Power Delivery 100 W + Universal Charger 100 W. Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 10,100,1000 Mbit/s. Product colour: Silver, Compatible memory cards: MicroSD (TransFlash), SD, Data transfer rate: 5 Gbit/s. Power source type: AC, AC input voltage: 100-240 V, AC input frequency: 50-60 Hz. Other operating systems supported: Android, ChromeOS

Ports & interfaces		Power	
Connectivity technology *	Wired	Output current	5 A
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Power consumption (max)	100 W
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	Compatible power plug types	UK
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	USB cable length	0.6 m
USB Power Delivery	✓	Software	
USB Power Delivery up to	100 W	Windows operating systems supported	✓
HDMI ports quantity *	1	Mac operating systems supported	✓
DisplayPorts quantity	2	Linux operating systems supported	✓
Combo headphone/mic port	✓	Other operating systems supported	Android, ChromeOS
Headphone connectivity	3.5 mm	Operational conditions	
Network		Operating temperature (T-T)	0 - 40 °C
Ethernet LAN *	✓	Operating relative humidity (H-H)	10 - 100%
Ethernet LAN (RJ-45) ports	1	Weight & dimensions	
Ethernet LAN data rates	10,100,1000 Mbit/s	Width	270 mm
Performance		Depth	85 mm
Card reader integrated *	✓	Height	23 mm
Compatible memory cards	MicroSD (TransFlash), SD	Weight	268 g
Data transfer rate	5 Gbit/s	Packaging data	
Number of displays supported	3	Package width	316 mm
Maximum refresh rate	60 Hz	Package depth	130 mm
Product colour *	Silver	Package height	30 mm
Housing material	Aluminium	Packaging content	
Power		AC adapter included	✓
Power source type	AC	Manual	✓
AC input voltage	100-240 V	Maximum notebook screen size compatibility	38.1 cm (15")
AC input frequency	50-60 Hz		
Input current	2.3 A		
Output voltage	5/9/12/15/19/20 V		



8595611706646

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-JUN-2024. Prints or copies of Information are only valid on the printed Publication date