i-tec USB-C Metal Ergonomic 3x 4K Display Docking Station + Power Delivery 100 W

Brand : i-tec

Product code: C31FLAT2PDPRO

Product name : USB-C Metal Ergonomic 3x 4K Display Docking Station + Power Delivery 100 W

- Docking station that can also be used as a laptop stand
- Compatible with USB-C and Thunderbolt laptops and tablets (Host device must support DisplayPort Alt mode)
- 2x DisplayPort and 1x HDMI support up to three external 4K displays or one 5K/60Hz display. (macOS only supports one extended display)
- Ergonomic design with aluminium housing, the dock has an integrated 60cm USB-C cable, making it suitable for use with all laptops & tablets with displays up to and including 15"
- Including 4x USB 3.2 ports and SD and microSD card slots makes it easy to connect multiple USB devices and peripherals
- Provides up to 100W Power Delivery for compatible laptops and tablets with USB-C and Thunderbolt (Host device must support USB-C Power Delivery)
- GLAN Ethernet supports network speeds of 10/100/1000 Mbps and provides robust, high-speed Internet connectivity
- Combined 3.5mm audio input/output for easy connection of headset or speakers
USB-C Metal Ergonomic 3x 4K Display Docking Station + Power Delivery 100 W

Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB Power Delivery	✔
USB Power Delivery up to	100 W
HDMI ports quantity *	1
DisplayPorts quantity	2
Combo headphone/mic port	✔

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s

Performance

Card reader integrated *	✔
Compatible memory cards	MicroSD (TransFlash), SD
Data transfer rate	5 Gbit/s
Number of displays supported	3
Product colour *	Silver

Power

USB cable length	0.6 m

Software

Windows operating systems supported	✔
Mac operating systems supported	✔
Linux operating systems supported	✔
Other operating systems supported	Android, ChromeOS

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 100%

Weight & dimensions

Width	270 mm
Depth	85 mm
Height	23 mm
Weight	268 g

Packaging data

Package width	316 mm
Package depth	130 mm
Package height	30 mm

Packaging content

AC adapter included	✘
Manual	✔

8595611706530