

POLY Trio C60 IP Conference Phone Full Radio and PoE-enabled

Brand: POLY Product code: 849B4AA

Product name : Trio C60 IP Conference Phone Full Radio and PoE-enabled

- Get more out of your conference calls. Poly reduces distracting background noise to ensure every inflection is heard. Hear every reaction with up to 22 kHz of rich, full sound.
- All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button thanks to the truly intuitive user experience.

Trio C60 IP Conference Phone Full Radio and PoE-enabled

POLY Trio C60 IP Conference Phone Full Radio and PoE-enabled:

One device. Many possibilities.

Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.

POLY Trio C60 IP Conference Phone Full Radio and PoE-enabled. Product type: IP conference phone, Product colour: Grey, Display type: LCD. USB connector type: Micro-USB B, USB Type-A. Sustainability certificates: ENERGY STAR. Width: 385 mm, Depth: 332 mm, Height: 75 mm





Features		Ports & interfaces	
Product type * Product colour Built-in display * Display type Display diagonal Display resolution	IP conference phone Grey ✓ LCD 12.7 cm (5") 720 x 1280 pixels G.711, G.719, G.722, G.722.1, G.722.1C, G.729ab, OPUS, iLBC ✓ Wi-Fi 4 (802.11n) 802.11b, 802.11g, Wi-Fi 4 (802.11n) ✓ 4.2 Gigabit Ethernet 10,100,1000 Mbit/s IEEE 802.1Q, IEEE 802.1p, IEEE 802.3af, IEEE 802.3at ✓ EAP-TLS, FIPS 140-2, MSCHAPv2, PEAP, TLS, WPA, WPA2, WPA2- Enterprise	USB port USB version USB connector type USB ports quantity Sustainability	✓ 2.0 Micro-USB B, USB Type-A 2
Voice codecs		Sustainability certificates Operational conditions	ENERGY STAR
Wi-Fi Top Wi-Fi standard Wi-Fi standards Bluetooth		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 70 °C 5 - 95%
Bluetooth version Ethernet interface type Ethernet LAN data rates Networking standards Power over Ethernet (PoE) Security algorithms Built-in speaker(s) *		Weight & dimensions Width Depth Height Weight Package width Package depth Package height Package weight	385 mm 332 mm 75 mm 950 g 483 mm 115 mm 394 mm
Ports & interfaces	,		
RJ-45 ports quantity	2		




























Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.