

Allied Telesis AT-2911SX/SC-901 network card Internal Fiber 1000 Mbit/s



Brand : Allied Telesis

Product code: AT-2911SX/SC-901

Product name : AT-2911SX/SC-901

1000BASE-SX Single-port Fiber NIC for PCIe x1 bus, SC connector, Federal/Government

[Allied Telesis AT-2911SX/SC-901 network card Internal Fiber 1000 Mbit/s:](#)

Allied Telesis AT-2911 Series Network Interface Cards feature a PCI Express (PCIe x1) design, providing the maximum possible bandwidth and bus efficiency while providing the benefits of low power consumption.

High Reliability

The AT-2911 Series Gigabit interface comes with a comprehensive Microsoft Windows utility which performs detailed tests, diagnostics and analysis.

Advanced Manageability

The priority queuing offered by the AT-2911 Series can help users set up the network based on their own needs. The comprehensive diagnostics and configuration software suite provides system administrators and engineers with a profound tool to analyze the interface card and check specific data. Allied Telesis AT-2911SX/SC-901. Internal. Connectivity technology: Wired, Host interface: PCI Express, Interface: Fiber. Maximum data transfer rate: 1000 Mbit/s

Ports & interfaces		System requirements	
Connectivity technology *	Wired	Windows operating systems supported	✓
Host interface *	PCI Express	Linux operating systems supported	✓
Interface *	Fiber	Operational conditions	
Fiber ports quantity	1	Operating temperature (T-T)	0 - 40 °C
Fiber optic connector	SC	Storage temperature (T-T)	-25 - 70 °C
Network		Operating relative humidity (H-H)	5 - 90%
Maximum data transfer rate *	1000 Mbit/s	Sustainability	
Networking standards *	IEEE 802.1p, IEEE 802.1Q, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Sustainability certificates	RoHS
	Fiber ethernet cabling technology	1000BASE-ZX	
	Jumbo frames support	✓	
	Quality of Service (QoS) support	✓	
	Design		Weight & dimensions
Internal *	✓	Width	87 mm
LED indicators	✓	Height	56 mm
Certification	UL FCC/EN55022 A TUV EN55024 CE C-TICK VCCI	Weight	700 g
		Logistics data	
Power	Output voltage 3.3 V Power consumption (typical) 9.2 W	Harmonized System (HS) code	85176990
		Other features	
		Flow control support	✓
		Management protocols	SNMP
		Link/Act LED	✓



0767035196619



767035196619

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.