

Epson WorkForce DS-6500N Flatbed scanner 1200 x 1200 DPI A4 White



Brand : Epson

Product code: B11B205231BU

Product name : WorkForce DS-6500N

WorkForce DS-6500N, 1200 dpi x 1200 dpi, Flatbed, ReadyScan LED, 3000 ppm, Mono: 25 p/min - Colour: 25 p/min, Ethernet

Epson WorkForce DS-6500N. Maximum scan size: 215.9 x 1.016 mm, Optical scanning resolution: 1200 x 1200 DPI, Input colour depth: 48 bit. Scanner type: Flatbed scanner, Product colour: White, Display: LCD.

Daily duty cycle (max): 3000 pages, Light source: ReadyScan LED, Scan file formats: JPG, PDF, TIFF.

Standard input capacity: 100 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Envelopes, Plain paper, Thin paper, Transparencies, ISO A-series sizes (A0...A9): A4



Scanning		Network	
Maximum scan size *	215.9 x 1.016 mm	Supported network protocols	TCP/IP, DHCP, DNS, SNMP, SLP, HTTP
Optical scanning resolution *	1200 x 1200 DPI	Features	
Colour scanning	✓	Country of origin	China
Duplex scanning *	✓	Packaging data	
Input colour depth	48 bit	Quantity per pack	1 pc(s)
Output colour depth	24 bit	Package width	495 mm
Film scanning	✗	Package depth	595 mm
ADF scan speed (b/w, A4)	25 ppm	Package height	320 mm
ADF scan speed (colour, A4)	25 ppm	Package weight	12.5 kg
Duplex ADF scan speed (b/w, A4)	50 ipm	System requirements	
Duplex ADF scan speed (colour, A4)	50 ipm	Windows operating systems supported	Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Design		Mac operating systems supported	✓
Scanner type *	Flatbed scanner	Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2008 R2
Product colour *	White	Operational conditions	
Display	LCD	Operating temperature (T-T)	5 - 35 °C
Built-in display *	✓	Storage temperature (T-T)	-25 - 60 °C
Performance		Operating relative humidity (H-H)	10 - 80%
Light source	ReadyScan LED	Storage relative humidity (H-H)	10 - 85%
Scan file formats	JPG, PDF, TIFF	Weight & dimensions	
Daily duty cycle (max) *	3000 pages	Width	495 mm
Scan drivers	ISIS, TWAIN, WIA	Depth	360 mm
Input capacity			
Standard input capacity	100 sheets		
Paper handling			
Scanning media types supported	Envelopes, Plain paper, Thin paper, Transparencies		
Maximum ISO A-series paper size *	A4		
ISO A-series sizes (A0...A9)	A4		
ISO B-series sizes (B0...B9)	B5		
Letter	✓		
Legal	✓		
Auto Document Feeder (ADF) media weight	50 - 128 g/m ²		
Ports & interfaces			
Standard interfaces	Ethernet		
Power			
Power supply type *	AC		
Power consumption (typical)	19 W		
Power consumption (standby)	4.8 W		
Power consumption (PowerSave)	15.5 W		

Power		Weight & dimensions	
AC input frequency	50 - 60 Hz	Height	217 mm
Input voltage	220-240 V	Weight	10.3 kg
Network		Packaging content	
Ethernet LAN	✓	Drivers included	✓
		Bundled software	ABBYY FineReader® Sprint 8.0 (MacOS), ABBYY FineReader® Sprint 9.0 (Windows), Epson Document Capture Pro (Windows only), Epson Document Capture Pro Server (on free download), Epson Event Manager (Mac Only), Epson Scan
Technical details			
Sustainability certificates		ENERGY STAR	
Logistics data			
Products per pallet		12 pc(s)	
Pallet gross length		120 cm	
Pallet gross width		80 cm	
Pallet gross height		157.8 cm	
Products per pallet layer		2 pc(s)	
Products per pallet layer (UK)		4 pc(s)	
Products per pallet (UK)		24 pc(s)	
Pallet length (UK)		120 cm	
Pallet width (UK)		100 cm	
Pallet height (UK)		157.8 cm	
Harmonized System (HS) code		84716070	



8715946510880

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-JUN-2024. Prints or copies of Information are only valid on the printed Publication date