

## APC SUA750RMI1U uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 480 W 4 AC outlet(s)

Brand : APC Product code: SUA750RMI1U

Product name: SUA750RMI1U

Smart-UPS 750VA USB RM 1U 230V

APC SUA750RMI1U uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 480 W 4 AC outlet(s):


## **Smart-UPS**

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

APC SUA750RMI1U. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 480 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 7.1 min, Typical backup time at half load: 23.6 min. Form factor: Rackmount, Product colour: Black, Grey, Rack capacity: 1U. Width: 432 mm, Depth: 660 mm, Height: 44 mm



Features		Battery	
Output power capacity * 0.7 Output power * 48 Waveform * 5in Input operation voltage (min) * 15: Input operation voltage (max) * 30: Input frequency * 50; Output operation voltage (min) 23: Output operation voltage (max) 23: Output frequency 57; Automatic Voltage Regulation (AVR) ✓ Surge energy rating 48:	480 J 55 dB	Typical backup time at full load Typical backup time at half load Hot-swap battery Automatic battery test	7.1 min 23.6 min ✓
		Design	
		Form factor * Rack capacity Product colour * LED indicators	Rackmount 1U Black, Grey Battery replacement
		Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m
Ports & interfaces		Non-operating altitude	0 - 15000 m
AC outlet types Power plug AC outlets quantity Number of output IEC jumpers USB port Serial interface Serial interface type SmartSlot	C13 coupler C14 coupler 4 AC outlet(s) 2   RS-232	Technical details	
		Sustainability certificates	RoHS
		Weight & dimensions  Width  Depth  Height  Weight	432 mm 660 mm 44 mm 21.8 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Rack mount kit Cables included Manual	√ RS-232, USB cable ✓
		Logistics data	
		Harmonized System (HS) code	85078000









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.