



## APC Smart-UPS 1500VA uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1000 W 4 AC outlet(s)



**Brand :** APC

**Product code:** SMT1500RM12UNC


**Product name :** Smart-UPS 1500VA

230 V, 1 KW / 1.5 kVA, 50/60 Hz, RJ-45, SmartSlot, USB, 480 x 683 x 86 mm, 44.19 kg  
 APC Smart-UPS 1500VA. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1000 W. AC outlet types: C13 coupler, C14 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 432 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 457 mm, Height: 89 mm

Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	1.5 kVA	Rack capacity	2U
Output power *	1000 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	151 V	LED indicators	✓
Input operation voltage (max) *	302 V	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Output voltage regulation	5%		
Surge energy rating	459 J		
Response time	2 ms		
Emergency Power Off (EPO)	0		
Noise level	46 dB		
Audible alarm(s)	✓		
Web-based management	✓		
Audible alarm modes	Battery replacement		
Auto-restart	✓		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler, C14 coupler	Operating temperature (T-T)	0 - 40 °C
Power plug	C14 coupler	Storage temperature (T-T)	-15 - 45 °C
AC outlets quantity	4 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
USB 2.0 ports quantity	1	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN (RJ-45) ports	1	Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
Battery		Technical details	
Battery technology	Sealed Lead Acid (VRLA)	Sustainability certificates	Green Premium, RoHS
Battery capacity	432 Ah		
Battery recharge time	3 h		
Hot-swap battery	✓		
Automatic battery test	✓		
Cold start	✓		
		Weight & dimensions	
		Width	432 mm
		Depth	457 mm
		Height	89 mm
		Weight	28.6 kg
		Package width	594 mm
		Package depth	603 mm
		Package height	251 mm
		Package weight	31.8 kg
		Packaging data	
		Rack mount kit	✓
		Cables included	Input power cable, USB cable
		Quick installation guide	✓
		Resource CD	✓
		Logistics data	
		Products per pallet	8 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	230 V



0731304327684



731304327684

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.