Canon

Canon imageFORMULA ScanFront 400 ADF scanner 600 x 600 DPI A4 Black, White

Brand : Canon

Product family: imageFORMULA

Product code: 1255C003

Product name : ScanFront 400

A4, ADF, CMOS CIS, RGB LED, 600 x 600DPI, 45ppm, Duplex, Ethernet,USB 2.0, touchscreen, 40W
Canon imageFORMULA ScanFront 400. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI, ADF scan speed (b/w, A4): 45 ppm. Scanner type: ADF scanner, Product colour: Black, White, Display: TFT. Sensor type: CMOS CIS, Daily duty cycle (max): 6000 pages, Light source: RGB LED. Auto document feeder (ADF) input capacity: 60 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), ISO A-series sizes (A0...A9): A4

Scanning

Maximum scan size *	216 x 356 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✓
Duplex scanning *	✓
Greyscale levels	256
ADF scan speed (b/w, A4)	45 ppm
ADF scan speed (colour, A4)	45 ppm

Design

Scanner type *	ADF scanner
Product colour *	Black, White
Display	TFT
Display diagonal	25.6 cm (10.1")
Display resolution	1024 x 600 pixels
Touchscreen	✓
Built-in display *	✓

Performance

Sensor type *	CMOS CIS
Light source	RGB LED
Scan file formats	PDF, PNG, TIFF
Daily duty cycle (max) *	6000 pages
Scan to	E-mail, FTP, Fax, USB

Input capacity

Auto document feeder (ADF) input capacity	60 sheets

Paper handling

Scanning media types supported	Business Card, Plastic Card, Post Card(JPN)
Maximum ISO A-series paper size *	A4
ISO A-series sizes (A0...A9)	A4
Media thickness (min)	0.04 mm

Paper handling

Auto Document Feeder (ADF) media weight	27 - 209 g/m²
Maximum scan width	21.6 cm
Maximum scan length	35.6 cm

Ports & interfaces

USB port *	✓
USB version	2.0
Standard interfaces	Ethernet, USB 2.0

Power

Power supply type *	AC
Power consumption (typical)	40 W
Power consumption (off)	0.5 W
AC input frequency	50 - 60 Hz
Input voltage	100-240 V

Network

Ethernet LAN	✓
Supported network protocols	TCP/IP (IPv4), DNS, DHCP, SMB, NTP, HTTP, FTP, SFTP, Secure sending (FTPS and SMTPS), WebDAV, LDAPS

Operational conditions

Operating temperature (T-T)	10 - 32.5 °C
Operating relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	305 mm
Depth	282 mm
Height	230 mm
Weight	4.5 kg

Technical details

Panel type	TFT
Sustainability certificates	RoHS, ENERGY STAR

Logistics data

Harmonized System (HS) code	84716070

4528472107110