

Epson TM-H6000V-216B1 180 x 180 DPI Wired Thermal POS printer

Brand : Epson

Product code: C31CG62216B1

Product name : TM-H6000V-216B1



Epson TM-H6000V-216B1. Print technology: Thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm. Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B, Standard interfaces: Ethernet, USB 1.1, USB 2.0. Ethernet LAN data rates: 10,100 Mbit/s. Sound pressure level (printing): 55 dB, Autocutter durability: 3 million cuts, Print head life: 200 km

Printing		Features	
Maximum resolution	180 x 180 DPI	Certification	CE, EN55024, EN55032 A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, 2014/30 / US
Print columns	40 dots/line		
Print speed	5.7 lps		
Print speed	350 mm/sec		
Character sets	ANK		
Print technology *	Thermal		
Type *	POS printer	Design	
Paper handling		Product colour *	Black
Maximum roll diameter	8.3 cm	Power	
Ports & interfaces		Power source type *	USB
USB port *	✓	DC output voltage	24 V
USB 2.0 ports quantity	2	Operational conditions	
USB connector	USB Type-A / USB Type-B	Operating temperature (T-T)	5 - 45 °C
Connectivity technology *	Wired	Storage temperature (T-T)	-10 - 50 °C
Ethernet LAN (RJ-45) ports	1	Operating relative humidity (H-H)	10 - 90%
Standard interfaces	Ethernet, USB 1.1, USB 2.0	Storage relative humidity (H-H)	10 - 90%
Network		System requirements	
Ethernet LAN *	✓	Pre-installed software	Server Direct Print, ePOS Display, ePOS-Print
Ethernet LAN data rates	10,100 Mbit/s	Weight & dimensions	
Wi-Fi *	✗	Width	186 mm
Features		Depth	278 mm
Sound pressure level (printing)	55 dB	Height	181 mm
Cutter	✓	Weight	4.4 kg
Autocutter durability	3 million cuts	Packaging data	
Print head life	200 km	Quantity per pack	1 pc(s)
Country of origin	China	Package width	295 mm
Ribbon life	4000000 million characters	Package depth	382 mm
Built-in sensors details	Middle of Paper pass sensor, Front cover open sensor (détecteur de couvercle avant ouvert), Roll paper cover open sensor, Paper End Sensor (détecteur de fin de rouleau), Top of Form sensor, Bottom of Form sensor (détecteur de bas de formulaire), Slip eject sensor, Receipt near-end sensor	Package height	293 mm
		Package weight	5.5 kg
		Packaging content	
		Quick start guide	✓
		Logistics data	
		Harmonized System (HS) code	84433210
		Other features	
		Buffer size	4 KB
		Print head life	20000000 million characters



8715946676111

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-JUN-2024. Prints or copies of Information are only valid on the printed Publication date