
Intellinet 16-Port Gigabit Ethernet PoE+ Switch, 16 x PoE ports, IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE), Endspan, **Rackmount (UK Power Cord)**



Brand: Intellinet Product code: 560993-UK

Product name: 16-Port Gigabit Ethernet PoE+ Switch, 16 x PoE ports, IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE),

Endspan, Rackmount (UK Power Cord)




- Saves time and money by delivering data and power via existing network cables
- 10/100/1000 auto-sensing ports automatically detect optimal network speeds
- IEEE 802.3at/af-compliant RJ45 PoE/PoE+ output ports
- Power output up to 30 watts per port*
- PoE power budget of 220 watts
- Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (wireless access points, VoIP phones, IP cameras)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- All RJ45 ports with Auto-MDIX (auto uplink) support
- Store and forward switching architecture
- IEEE 802.3x flow control for full duplex
- Supports up to 8192 MAC address entries
- 256 kBytes buffer memory
- Two high-volume cooling fans ensure perfect ventilation
- Includes 19" rackmount brackets
- Three-Year Warranty

16-Port Gigabit Ethernet PoE+ Switch, 16 x PoE ports, IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE), Endspan, Rackmount (UK 3-pin plug)

Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity * Basic switching RJ-45 Ethernet ports type *		AC input voltage AC input frequency Power consumption (max)	100 - 240 V 50 - 60 Hz 260 W
Power connector	DC-in jack	Power over Ethernet (PoE)	
Network Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u,	Power over Ethernet (PoE) * Power over Ethernet (PoE) type supported	✓ PoE+
IEEE 802.3x		Operational conditions	
10G support * Copper ethernet cabling technology Full duplex	X 10BASE-T, 100BASE-TX, 1000BASE-T T √	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 70 °C 10 - 90%
Data transmission		Weight & dimensions	
Switching capacity * MAC address table * Store-and-forward	32 Gbit/s 8192 entries ✓	Width Depth Height Weight	442 mm 208 mm 44 mm 3.8 kg
Design		Packaging data	
Rack mounting * Product colour Housing material LED indicators Certification	✓ BlackMetal✓ FCC Class B, VCCI Class A, CE, RoHS	Cables included Manual Package type Rack mount kit	AC Box





766623995764

0766623995764

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.