



APC SRT1000XLI uninterruptible power supply (UPS) Double-conversion (Online) 1 kVA 1000 W 12 AC outlet(s)

Brand : APC

Product code: SRT1000XLI

Product name : SRT1000XLI

Smart-UPS SRT 1000VA 230V

APC SRT1000XLI. UPS topology: Double-conversion (Online), Output power capacity: 1 kVA, Output power: 1000 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 12 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 48 V, Typical backup time at full load: 8 min. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Width: 85 mm, Depth: 505 mm, Height: 432 mm




Features		Battery	
UPS topology *	Double-conversion (Online)	Hot-swap battery	✓
Output power capacity *	1 kVA	Automatic battery test	✓
Output power *	1000 W	Cold start	✓
Waveform *	Sine		
Input operation voltage (min) *	220 V		
Input operation voltage (max) *	240 V		
Input frequency *	40/70 Hz		
Output operation voltage (min)	50 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Surge energy rating	432 J		
Crest factor	3:1		
ECO mode	✓		
Emergency Power Off (EPO)	✓		
Output voltage Total Harmonic Distortion (THD)	2%		
Noise level	50 dB		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Battery replacement		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler	Form factor *	Rackmount/Tower
Power plug	C14 coupler	Rack capacity	2U
AC outlets quantity	12 AC outlet(s)	Cable length	1.8 m
USB port	✓	Cooling type	Active
Serial interface	✓	Built-in fan	✓
Serial interface type	RJ-45	Product colour *	Black
Serial ports quantity	1	Display type	LCD
SmartSlot	✓	LED indicators	✓
		International Protection (IP) code	IP20
		Certification	CE, EAC
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-20 - 50 °C
		Operating relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3048 m
		Non-operating altitude	0 - 15240 m
		Technical details	
		Sustainability compliance	✓
		Sustainability certificates	CE, Green Premium
		Weight & dimensions	
		Width	85 mm
		Depth	505 mm
		Height	432 mm
		Weight	20.5 kg

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Battery width	59.4 cm
Battery voltage	48 V	Battery depth	74.9 cm
Typical backup time at full load	8 min	Battery height	24.6 cm
Typical backup time at half load	21 min	Battery weight	29.6 kg
Battery life (max)	5 year(s)	Packaging data	
Battery recharge time	3 h	Cables included	USB cable
		Quick installation guide	✓
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304340270



731304340270

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.