



EIZO FlexScan EV3895-BK LED display 95.2 cm (37.5") 3840 x 1600 pixels UltraWide Quad HD+ Black

Brand : EIZO

Product family: FlexScan

Product code: EV3895-BK

Product name : EV3895-BK



37.5" UWQHD+ (3840 x 1600), 24:10, 300 cd/m², 2300R, 1000:1, USB-C, HDMI, DisplayPort, LAN, KVM Switch, 29 kWh/1000h, E

EIZO FlexScan EV3895-BK. Display diagonal: 95.2 cm (37.5"), Display resolution: 3840 x 1600 pixels, HD type: UltraWide Quad HD+, Display technology: LED, Response time: 5 ms, Native aspect ratio: 24:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	95.2 cm (37.5")	Headphone outputs	1
Display resolution *	3840 x 1600 pixels	Headphone connectivity	3.5 mm
HD type *	UltraWide Quad HD+	Built-in KVM switch	✓
Native aspect ratio *	24:10	HDCP	✓
Display technology *	LED	Network	
Panel type *	IPS	Ethernet LAN	✓
Backlight type	LED	Ergonomics	
Touchscreen *	✗	VESA mounting *	✓
Display brightness (typical)	300 cd/m ²	Panel mounting interface	100 x 100 mm
Response time	5 ms	Cable lock slot *	✓
Screen shape *	Curved	Cable lock slot type	Kensington
Screen curvature rating	2300R	Height adjustment *	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1440, 2560 x 1600 (WQXGA), 3440 x 1440, 3840 x 1600	Height adjustment	19.3 cm
		Swivelling	✓
		Swivel angle range	-70 - 70°
		Tilt adjustment	✓
		Tilt angle range	-5 - 35°
Contrast ratio (typical) *	1000:1	On Screen Display (OSD)	✓
Maximum refresh rate *	60 Hz	On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Swedish
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Energy efficiency class (SDR) *	E
Display number of colours *	16.78 million colours	Energy consumption (SDR) per 1000 hours *	29 kWh
Pixel pitch	0.229 x 0.229 mm	Power consumption (typical) *	29 W
Pixel density	111 ppi	Power consumption (standby) *	0.5 W
Viewable size, horizontal	88 cm	Power consumption (max)	194 W
Viewable size, vertical	36.6 cm	AC input voltage	100 - 240 V
Viewable size diagonal	95.3 cm		
Digital horizontal frequency	31 - 99 kHz		

Display		Power	
Digital vertical frequency	29 - 31 Hz	AC input frequency	50 - 60 Hz
Colour gamut standard	sRGB	Energy efficiency scale	A to G
Performance		Operational conditions	
NVIDIA G-SYNC *	✗	Operating temperature (T-T)	5 - 35 °C
AMD FreeSync *	✗	Storage temperature (T-T)	-20 - 60 °C
Flicker-free technology	✓	Operating relative humidity (H-H)	20 - 80%
Low Blue Light technology	✓	Storage relative humidity (H-H)	10 - 90%
Multimedia		Packaging content	
Built-in speaker(s) *	✓	Stand included	✓
Number of speakers	2	Cables included	AC, DisplayPort, HDMI, USB Type-A to USB Type-B, USB Type-C to USB Type-C
RMS rated power	2 W	Quick start guide	✓
Design		Weight & dimensions	
Market positioning *	Business	Width (with stand)	893.9 mm
Product colour *	Black	Depth (with stand)	240 mm
	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified	Height (with stand)	411 mm
	Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC	Weight (with stand)	13.2 kg
Certification		Width (without stand)	893.9 mm
		Depth (without stand)	109.8 mm
		Height (without stand)	398.2 mm
		Weight (without stand)	9.5 kg
Ports & interfaces		Sustainability	
Built-in USB hub *	✓	Sustainability compliance	✓
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Sustainability certificates	ENERGY STAR, EPEAT Climate +, EPEAT Silver, TCO
USB upstream port type	USB Type-B, USB Type-C	European Product Registry for Energy Labelling (EPREL) code	356891
Number of USB Type-B upstream ports quantity	2		
Number of USB Type-C upstream ports quantity	1	Logistics data	
USB Type-A downstream ports quantity	4	Harmonized System (HS) code	85285210
USB Type-C DisplayPort Alternate Mode	✓	Other features	
DVI port	✗	Picture-by-Picture (PbP)	✓
HDMI *	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
HDMI ports quantity	2	Ethernet LAN (RJ-45) ports	1
DisplayPorts quantity	1		
Headphone out *	✓		



4995047056737



0690592049763



690592049763

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.