

## BenQ MH5005 data projector Standard throw projector 3800 ANSI lumens DLP 1080p (1920x1080) White

Brand : BenQ Product code: 9H.JNG77.13G

**Product name : MH5005** 

Benq (in)

- 3800 ANSI Lumen High brightness and 20000:1 High Contrast
- Exclusive Data Review Mode Showcases Text and Charts in Detail
- SmartEco Mode Saves Lamp Power Up To 70%

1080P Business Projector For Presentation, DLP, 3800 ANSI Lumen, 1920 x 1080, 16:9, 20000: 1 BenQ MH5005. Projector brightness: 3800 ANSI lumens, Projection technology: DLP, Projector native resolution: 1080p (1920x1080). Light source type: Lamp, Service life of light source: 6000 h, Service life of light source (economic mode): 10000 h. Throw ratio: 1.49-1.64:1, Offset: 110%. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1200 (WUXGA), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232



Projector		Network	
Screen size compatibility * Projector brightness * Projection technology *	1778 - 3810 mm (70 - 150") 3800 ANSI lumens DLP	Smart TV * Ethernet LAN *	x x
		Features	
Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colours Horizontal scan range Vertical scan range Keystone correction, vertical Matrix size Matrix type	1080p (1920x1080) 20000:1 16:9 1.07 billion colours 15 - 102 kHz 23 - 120 Hz -40 - 40° 1.65 cm (0.65")	Noise level (economic mode) On Screen Display (OSD) On Screen Display (OSD) languages	29 dB  Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese
Light source		Number of OSD languages	30
Light source type *	Lamp	Noise level *	32 dB
Service life of light source * Service life of light source	6000 h	Multimedia	
(economic mode)	10000 h	Built-in speaker(s) *	✓
Lamps quantity	1 lamp(s)	RMS rated power	10 W
Lens system		Number of built-in speakers	1
Throw ratio	1.49-1.64:1	Design	
Offset	110%	Market positioning *  Product type *	Presentation
Video		Product type *  Product colour *	Standard throw projector White
Analog signal format system * Full HD *	NTSC, PAL, SECAM ✓	Power	
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1200 (WUXGA)	Power source * Power consumption (typical) *	AC 260 W
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	Power consumption (standby) * Power consumption (max)	0.5 W 280 W
Ports & interfaces		Power consumption (economy mode)	215 W
S-Video inputs quantity	1	,	
USB 2.0 ports quantity *	1	Operational conditions	0. 40.00
Mini-USB 2.0 ports quantity	1	Operating temperature (T-T)	0 - 40 °C

Ports & interfaces		Weight & dimensions	
Headphone outputs Serial interface type * PC Audio in VGA (D-Sub) ports quantity * HDMI ports quantity * Composite video in * DVI port *	1 RS-232 ✓ 2 2 1	Width Depth Height Weight *  Packaging content	296 mm 221 mm 120 mm 2.3 kg
		Remote control included * Remote control type Batteries included Cables included	✓ IR ✓ AC, VGA
		Logistics data	
		Quantity per pack Harmonized System (HS) code	1 pc(s) 85286200

