Viewsonic PG707X data projector Standard throw projector 4000 ANSI lumens DMD XGA (1024x768) White

Brand : Viewsonic

Product name : PG707X

Product code: PG707X

XGA 1024 x 768, 4000 Lm, 20000 h, 22000:1, 4:3, DLP Lamp, USB, RJ45, Audio in/out, HDMI, VGA, 2.4 kg
Viewsonic PG707X. Projector brightness: 4000 ANSI lumens, Projection technology: DMD, Projector native resolution: XGA (1024x768). Light source type: Lamp, Service life of light source: 6000 h, Service life of light source (economic mode): 20000 h. Focus: Manual, Focal length range: 16.88 - 21.88 mm, Aperture range (F-F): 2.59 - 2.87. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1080 (HD 1080), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size

Projector

Screen size compatibility *	762 - 7620 mm (30 - 300")
Projection distance	0.9 - 12 m
Projector brightness *	4000 ANSI lumens
Projection technology *	DMD
Projector native resolution *	XGA (1024x768)
Contrast ratio (typical) *	22000:1
Number of colours	1.07 billion colours
Horizontal scan range	15 - 102 kHz
Vertical scan range	23 - 120 Hz
Keystone correction, horizontal	-40 - 40°
Keystone correction, vertical	-40 - 40°
Matrix size	1.4 cm (0.55")

Light source

Light source type *	Lamp
Service life of light source *	6000 h
Service life of light source (economic mode)	20000 h
Lamp power	203 W
Lamps quantity	1 lamp(s)

Lens system

Focus *	Manual
Focal length range	16.88 - 21.88 mm
Aperture range (F-F)	2.59 - 2.87
Zoom capability	✓
Zoom ratio	2.0:1
Throw ratio	1.51-1.97
Offset	115%

Video

Analog signal format system *	NTSC, PAL, SECAM
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1080 (HD 1080)
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Ports & interfaces

HDMI connector type	Full-size

Network

Smart TV *	✗
Ethernet LAN *	✓
Ethernet LAN (RJ-45) ports	1
Wi-Fi *	✗

Storage

Card reader integrated *	✗

Features

Interactive *	✗
Noise level (economic mode)	28 dB
HDCP	✓
On Screen Display (OSD)	✓
On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Thai, Turkish, Vietnamese
Number of OSD languages	23
Noise level *	32 dB

Multimedia

Built-in speaker(s) *	✓
RMS rated power	10 W

Design

Market positioning *	Presentation
Product type *	Standard throw projector
Product colour *	White
Placement	Desktop, Ceiling

Display

Built-in display *	✗

Power

Power source *	AC
Power consumption (typical) *	280 W
Power consumption (standby) *	0.5 W
AC input voltage	100-240 V

Ports & interfaces

HDMI version	1.4
USB 2.0 ports quantity *	1
Serial interface type *	RS-232
PC Audio in	✔
PC Audio out	✔
VGA (D-Sub) ports quantity *	2
HDMI ports quantity *	2
Composite video in *	1
DVI port *	✘
AC (power) in	✔

Power

AC input frequency	50 - 60 Hz

Operational conditions

Operating temperature (T-T)	0 - 40 °C

Weight & dimensions

Width	294 mm
Depth	218 mm
Height	110 mm
Weight *	2.35 kg
Package width	415 mm
Package depth	168 mm
Package height	297 mm
Package weight	3.56 kg

Packaging content

Remote control included *	✔
Cables included	AC, VGA
Manual	✔

Logistics data

Harmonized System (HS) code	85286200

0766907006193

766907006193