



Biamp Desono DX-S8 Two-Way High Output Coaxial 8-inch Surface Mount Loudspeaker ClickMount White



Brand : Biamp

Product family: Desono

Product code: 910.0110.900

Product name : DX-S8 Two-Way High Output Coaxial 8-inch Surface Mount Loudspeaker ClickMount White

DX-S8 Two-Way High Output Coaxial 8-inch Surface Mount Loudspeaker ClickMount White

[Biamp Desono DX-S8 Two-Way High Output Coaxial 8-inch Surface Mount Loudspeaker ClickMount White:](#)

The Desono™ DX surface mount loudspeakers provide high efficiency, high output, high intelligibility and low distortion in an attractive design. These loudspeakers install quickly and have the same components and voicing as the DX ceiling loudspeakers. The DX surface mount loudspeakers are equipped with a built-in 70 V/100 V autoformer and low impedance input.

For larger installations, the 8" coaxial DX-S8 provides higher sound pressure levels, higher sensitivity and greater bass extension. The DX-S8 also easily outperforms competitive 10" format loudspeakers. With a modern appearance that merges well in most environments, combined with weather-resistant capability suitable for direct outdoor use, the DX-S8 can be used in a wide variety of speech and music applications.

Certified for use with Zoom software.

Loudspeakers		Amplifier	
Speaker type *	2-way	Amplifier *	✗
Speaker placement *	Surface-mountable	Recommended amplifier power (max)	350 W
Tweeter	✓	Recommended amplifier power (min)	175 W
Number of tweeter drivers	1	Ports & interfaces	
Tweeter diameter	3.2 cm	Connectivity technology *	Wired
Tweeter diameter (imperial)	3.18 cm (1.25")	Bluetooth *	✗
Woofers	✓	Weight & dimensions	
Number of woofer drivers	1	Width	255 mm
Woofer diameter	20.3 cm	Depth	260 mm
Woofer diameter (imperial)	20.3 cm (8")	Height	385 mm
Audio		Weight	7.71 kg
RMS rated power *	175 W	Packaging data	
Frequency range	62 - 18000 Hz	Package width	810.3 mm
Impedance	7 Ω	Package depth	439.4 mm
Sensitivity	95 dB	Package height	340.4 mm
Crossover frequency	1400 Hz	Package weight	15.5 kg
Sound pressure level (max)	122 dB	Packaging content	
Input sensitivity	2830 mV	Mounting brackets included	✓
Performance		Logistics data	
Recommended usage *	Universal	Export Control Classification Number (ECCN)	EAR99
Product colour *	White	Harmonized System (HS) code	8518210000
International Protection (IP) code	IP54	Other features	
Suitable for outdoor use	✓	Country of origin	United States

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-JUN-2024. Prints or copies of Information are only valid on the printed Publication date