

## Biamp Desono COLW81 loudspeaker 2-way White Wired 80 W

**Brand :** Biamp      **Product family:** Desono      **Product code:** 911.1593.900  
**Product name :** COLW81

165 - 17000 Hz, 100 x 10°, 8x 3.3", 1x 1", 974 x 100 x 83 mm, White

[Biamp Desono COLW81 loudspeaker 2-way White Wired 80 W:](#)

The COLW81 offers excellent audio directivity for music as well as speech. Thanks to the elegant design, this speaker is ideal for indoor and outdoor use: from sports fields to public buildings or recreational areas, meeting rooms, or educational facilities.

These column speakers offer the perfect combination of looks and acoustical quality. The COLW41 has 8 x 3, 3" woofers and 1 x 1" tweeter. A standard wall bracket and installation tools are included.

The COLW81 loudspeakers can be painted any color.

Certified for use with Zoom software  
 Biamp Desono COLW81. Recommended usage: Universal. Speaker type: 2-way, Number of drivers: 9. Connectivity technology: Wired. RMS rated power: 80 W, Frequency range: 165 - 17000 Hz, Impedance: 8 Ω, Sensitivity: 97 dB. Product colour: White

Loudspeakers		Performance	
Speaker type *	2-way	International Protection (IP) code	IP66
Speaker placement *	Wall-mountable	Suitable for outdoor use	✓
Number of drivers *	9	Certification	Zoom
Number of mid-range drivers	8	<b>Amplifier</b>	
Mid-range driver diameter (imperial)	8.38 cm (3.3")	Amplifier *	✗
Tweeter	✓	<b>Ports &amp; interfaces</b>	
Number of tweeter drivers	1	Connectivity technology *	Wired
Tweeter diameter (imperial)	2.54 cm (1")	Bluetooth *	✗
<b>Audio</b>		<b>Packaging data</b>	
RMS rated power *	80 W	Package width	145 mm
Peak Music Power Output (PMPO)	320 W	Package depth	1020.1 mm
Frequency range	165 - 17000 Hz	Package height	169.9 mm
Impedance	8 Ω	Package weight	7.05 kg
Sensitivity	97 dB	<b>Packaging content</b>	
Sound pressure level (max)	122 dB	Quantity per pack	1 pc(s)
<b>Performance</b>		<b>Logistics data</b>	
Recommended usage *	Universal	Export Control Classification Number (ECCN)	EAR99
Product colour *	White	Harmonized System (HS) code	8518220000
		<b>Other features</b>	
		Country of origin	China



5420035212844

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-JUN-2024. Prints or copies of Information are only valid on the printed Publication date