

Origin Storage 3TB 7.2k PowerEdge R/T x10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB

Brand : Origin Storage Product code: DELL-3000NLS/7-S11

Product name : 3TB 7.2k PowerEdge R/T x10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB

- Does not invalidate OEM warranty
- 100% compatible replacement/upgrade for storage solutions
- Pre- & Post-Sale UK Based Tech Support

3TB 7.2k PowerEdge R/T x10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB

Origin Storage 3TB 7.2k PowerEdge R/T \times 10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB:

Origin Storage Ltd manufactures a full range of Matched Hard Drive & Solid State Solutions for most major branded Servers, laptops and desktops, such as Dell, HP, Toshiba, and Lenovo. All of our Matched Drive Solutions come with up to 5 years advanced replacement warranty and also come with free pre and post sales technical support. We can supply replacements or upgrades in form factors of 2.5" or 3.5" with either SATA or SAS interfaces, available in a range of capacities and spin speeds. All our Matched Drive Solutions are just that, matched to the system you have for 100% compatibility, right first time, every time!

Origin Storage 3TB 7.2k PowerEdge R/T x10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB. HDD size: 3.5", HDD capacity: 4 TB, HDD speed: 7200 RPM



Features		Operational conditions	
HDD size * HDD capacity * HDD speed * Interface * Type * Component for * Hot-swap *	3.5" 4 TB 7200 RPM SAS HDD Server/workstation	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating vibration Non-operating vibration Operating altitude Non-operating altitude Operating shock	5 - 95% 5 - 95% 0.5 G 0.25 G -304.8 - 3048 m -304.8 - 12192 m 70 G
Storage drive buffer size HDD interface transfer rate Average latency Bytes per sector Mean time between failures (MTBF) Refurbished	128 MB 6 Gbit/s 4.16 ms 512 2000000 h	Non-operating shock Technical details Sustainability certificates Weight & dimensions Width	300 G RoHS
Power Power consumption (typical) Power consumption (idle) Operating voltage	10.72 W 6.74 W 5 / 12 V	Height Depth Weight Packaging data	26.1 mm 147 mm 850 g
Operational conditions Operating temperature (T-T) Storage temperature (T-T)	5 - 55 °C -40 - 70 °C	Storage drive adapter included Logistics data Harmonized System (HS) code	X 84717050





5055146573586

5054484202950

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.