StarTech.com 4-Port PCI Express USB 3.0 Card

Brand : StarTech.com **Product code:** PEXUSB3S42

Product name: 4-Port PCI Express USB 3.0 Card

 $StarTech.com\ 4\ Port\ PCI\ Express\ USB\ 3.0\ Card\ -\ 3\ External\ and\ 1\ Internal\ -\ Native\ OS\ Support\ in\ Windows\ 8\ and\ 7\ -\ Standard\ and\ Low-Profile$

StarTech.com 4-Port PCI Express USB 3.0 Card. Host interface: PCle, Output interface: USB 3.2 Gen 1 (3.1 Gen 1), Expansion card form factor: Full-height / Low-profile. Product colour: Black, Stainless steel, Maximum cable length: 3 m, Certification: CE, FCC. Chipset: 2 x Renesas / NEC - μ PD720202, Data transfer rate (max): 5 Gbit/s. Windows operating systems supported: Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64,..., Server operating systems supported: Windows Server 2008 R2, Windows Server 2012. Width: 15 mm, Depth: 167 mm, Height: 120 mm





| Ports & interfaces | | System requirements | |
|----------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Host interface * Output interface * Expansion card form factor Expansion card standard USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | PCIe USB 3.2 Gen 1 (3.1 Gen 1) Full-height / Low-profile PCI 2.0 | Education x64, Wi Enterprise, Window x64, Windows 10 H 10 Home x64, Win Windows 10 Pro x6 Enterprise, Window | Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, |
| Design | | Windows 7 Home Basic x64, | |
| Internal * Product colour Maximum cable length Hot-swap Certification | ✓Black, Stainless steel3 m✓CE, FCC | Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Window | |
| Features | | Windows operating systems 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro | |
| Chipset Data transfer rate (max) UASP support | 2 x Renesas / NEC - μPD720202 5 Gbit/s | x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows | |
| Operational conditions | | | 8.1 x64, Windows Vista Business, Windows Vista Business x64. |
| Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 5 - 50 °C -20 - 60 °C 20 - 80% | Windows Vista Enterprise Vista Enterprise x64, Wir Home Basic, Windows Vista Basic x64, Windows Vista Premium, Windows Vista Premium x64, Windows Vista X64, Windows XP Home, XP Home x64, Windows XP | Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional, Windows XP Professional x64 |
| | | Linux operating systems supported | ✓ |
| | | Server operating systems supported | Windows Server 2008 R2, Windows Server 2012 |
| | | Technical details | |
| | | Sustainability certificates | RoHS |

| Weight & dimensions | | | | |
|-----------------------------|----------|--|--|--|
| Width | 15 mm | | | |
| Depth | 167 mm | | | |
| Height | 120 mm | | | |
| Weight | 90 g | | | |
| Packaging data | | | | |
| Mounting brackets included | 1 | | | |
| Drivers included | ✓ | | | |
| Manual | ✓ | | | |
| Package width | 171 mm | | | |
| Package depth | 144 mm | | | |
| Package height | 30 mm | | | |
| Package weight | 141 g | | | |
| Logistics data | | | | |
| Harmonized System (HS) code | 84733020 | | | |









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.