

Gigabyte UD1000GM power supply unit 1000 W 20+4 pin ATX ATX Black


Brand : Gigabyte

Product code: GP-UD1000GM

Product name : UD1000GM

1000W, Active PFC, 120mm Hydraulic bearing fan, 80 PLUS Gold

Gigabyte UD1000GM. Total power: 1000 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, CPU power cable length: 60 cm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Fan diameter: 12 cm, Number of fans: 1 fan(s). Cables included: CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	1000 W	CPU power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	CPU power cable length	60 cm
AC input frequency	50 - 60 Hz	ATX power connector (20+4 pin)	✓
Input current	15 - 6.5 A	Floppy drive power connector	1
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Combined power (+3.3V)	125 W	Performance	
Combined power (+12V)	999.6 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5V)	125 W	Purpose *	PC
Combined power (-12V)	3.6 W	Power supply unit (PSU) form factor	ATX
Combined power (+5Vsb)	15 W	* Bearing technology	HDB
Max output current (+3.3V)	25 A	Mean time between failures (MTBF)	100000 h
Max output current (+12V)	83.3 A	Design	
Max output current (+5V)	25 A	Product colour	Black
Max output current (-12V)	0.3 A	Fan diameter	12 cm
Max output current (+5Vsb)	3 A	Number of fans	1 fan(s)
Hold time	16 ms	Fan location	Top
Efficiency	90%	On/off switch	✓
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage	Packaging content	
Ports & interfaces		Cables included	CPU, PCIe, Peripheral (Molex), SATA
Motherboard power connector *	20+4 pin ATX	Weight & dimensions	
Motherboard power cable length	61 cm	Width	140 mm
Number of SATA power connectors	8	Depth	150 mm
Peripheral (Molex) power connectors (4-pin) *	3	Height	86 mm
EPS power connector (4+4 pin)	✓	Packaging data	
PCI Express power connectors (6+2 pin)	6	Package type	Box
		Logistics data	
		Harmonized System (HS) code	84733020



4719331552411



4719331552428

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.