

## StarTech.com Fiber Media Converter Gigabit 1000Mbps MM Fibre LC 550m

**Brand :** StarTech.com

**Product code:** ET91000LC2

**Product name :** Fiber Media Converter Gigabit 1000Mbps MM Fibre LC 550m



StarTech.com Multimode (MM) LC Fiber Media Converter for 1Gbe Network - 550m Range - Gigabit Ethernet - 850nm - with SFP Transceiver (ET91000LC2)

StarTech.com Fiber Media Converter Gigabit 1000Mbps MM Fibre LC 550m. Maximum data transfer rate: 2000 Mbit/s, Converter input interface: 1000Base-T, Converter output interface: 1000Base-LX, 1000Base-SX. Fiber optic connector: LC, Connectivity technology: Wired. Maximum transfer distance: 550 m, Wavelength: 850 nm, Fiber mode structure: Multi-mode. Product colour: Black, Certification: CE, FCC. Output voltage: 12 V, Output current: 1 A, Power consumption (typical): 4 W



<b>Network</b>		<b>Power</b>	
Maximum data transfer rate *	2000 Mbit/s	Output current	1 A
Converter input interface	1000Base-T	Power consumption (typical)	4 W
Converter output interface	1000Base-LX, 1000Base-SX	External power adapter	✓
Ethernet interface type	Gigabit Ethernet	<b>Management features</b>	
Ethernet LAN data rates	1000 Mbit/s	Plug and Play	✓
Auto MDI/MDI-X	✓	<b>Weight &amp; dimensions</b>	
Duplex system	Full, Half	Weight	620 g
<b>Ports &amp; interfaces</b>		<b>Operational conditions</b>	
Connectivity technology	Wired	Operating temperature (T-T)	0 - 60 °C
Ethernet LAN (RJ-45) ports	1	Storage temperature (T-T)	-10 - 70 °C
Fiber ports quantity	1	Operating relative humidity (H-H)	10 - 90%
Fiber optic connector *	LC	<b>Packaging data</b>	
DC-in jack	✓	Package width	206 mm
<b>Performance</b>		Package depth	138 mm
Maximum transfer distance *	550 m	Package height	89 mm
Wavelength *	850 nm	Package weight	774 g
Fiber mode structure	Multi-mode	<b>Packaging content</b>	
Mean time between failures (MTBF)	65000 h	Manual	✓
<b>Design</b>		<b>Technical details</b>	
Internal *	✗	Sustainability certificates	RoHS
Product colour	Black	<b>Logistics data</b>	
Certification	CE, FCC	Harmonized System (HS) code	85176990
<b>Power</b>		<b>Other features</b>	
Output voltage	12 V	Dimensions (WxDxH)	95 x 160 x 20 mm
		Full duplex	✓



0065030846226



065030846226

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.