

## APC SMC1500IC uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 900 W 8 AC outlet(s)

Brand : APC

Product code: SMC1500IC

Product name : SMC1500IC

## 1.5 kVA, 900W, 170-300V, 50/60Hz, 459J, 171x439x219mm, 24.09kg, Black

APC SMC1500IC. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 900 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Mini Tower, Product colour: Black, Display type: LCD. Width: 171 mm, Depth: 439 mm, Height: 219 mm





Features		Battery	
UPS topology *Line-InteractiveOutput power capacity *1.5 kVAOutput power *900 WWaveform *SineInput operation voltage (min) *170 V	Battery life (max) Battery recharge time Hot-swap battery Automatic battery test Cold start	5 year(s) 3 h ✔ ✔	
Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency Automatic Voltage Regulation (AVR)	300 V 50/60 Hz 220 V 240 V 50/60 Hz	Design Form factor * Product colour * Display type LED indicators	Mini Tower Black LCD
Surge energy rating Output voltage Total Harmonic Distortion (THD)	459 J 5%	Certification Operational conditions	C-tick, CE, CSA, GOST, UL 1778, VDE
Noise level Audible alarm(s) Web-based management Audible alarm modes Auto-restart	alarm, Overload alarm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Temperature voltage compensation       ✓         Ports & interfaces       ✓         AC outlet types       C13 coupler	Technical details Sustainability certificates	Green Premium	
Power plug AC outlets quantity USB port USB 2.0 ports quantity Serial interface Serial ports quantity	C14 coupler 8 AC outlet(s) 1 1 1	Weight & dimensions Width Depth Height Weight Package width Package depth Package height	171 mm 439 mm 219 mm 24.1 kg 328 mm 595 mm 376 mm

## Battery

Battery technology Number of batteries supported Sealed Lead Acid (VRLA) 1

## Packaging data

Packaging uala	
Cables included	USB cable
Resource CD	✓
Software CD	✓
Package volume	27230 cm <sup>3</sup>
Logistics data	
Products per pallet	18 pc(s)
Harmonized System (HS) code	85078000





731304332961

0731304332961

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.