

Manhattan Charging Cabinet/Cart via USB-C x20 Devices, Desktop, Power Delivery 18W per port (360W total), Suitable for iPads/other tablets/phones, Bays 264x22x235mm, Device charging cables not included, Silent Ventilation, Lockable (2 keys), EU & UK power cords



Brand : Manhattan

Product code: 715959

Product name : Charging Cabinet/Cart via USB-C x20 Devices, Desktop, Power Delivery 18W per port (360W total), Suitable for iPads/other tablets/phones, Bays 264x22x235mm, Device charging cables not included, Silent Ventilation, Lockable (2 keys), EU & UK power cords

Charging Cabinet via USB-C x20 Devices, Desktop, Power Delivery 3A/18W per port (360W total), Suitable for iPads/other tablets/phones, Bays 264x22x235mm, Device charging cables not included, Silent Ventilation, Lockable (2 keys), Euro 2-pin Plug

Manhattan Charging Cabinet/Cart via USB-C x20 Devices, Desktop, Power Delivery 18W per port (360W total), Suitable for iPads/other tablets/phones, Bays 264x22x235mm, Device charging cables not included, Silent Ventilation, Lockable (2 keys), EU & UK power cords. Type: Portable device management cabinet, Product colour: Black, Placement: Table. Supported portable devices: Smartphone, Tablet, Device connectors supported: USB, Charging source: USB Type-C. AC input voltage: 110 - 240 V, AC input frequency: 50 - 60 Hz, Output voltage: 5 - 12 V. Width: 370 mm, Depth: 610 mm, Height: 345 mm. Cables included: AC, Number of keys included: 2 pc(s)

Design		Power	
Type *	Portable device management cabinet	AC input voltage	110 - 240 V
Placement	Table	AC input frequency	50 - 60 Hz
Cord length	2 m	Output voltage	5 - 12 V
Product colour *	Black	Operational conditions	
Housing material	Metal	Operating temperature (T-T)	0 - 40 °C
Features		Operating relative humidity (H-H)	20 - 80%
Number of devices supported *	20	Storage temperature (T-T)	-15 - 45 °C
Supported portable devices *	Smartphone, Tablet	Weight & dimensions	
Charging source	USB Type-C	Width	370 mm
Device connectors supported *	USB	Depth	610 mm
Power protection features	Over current, Over voltage, Short circuit	Height	345 mm
LED indicators	Status	Weight	18 kg
Locking	✓	Housing thickness	1.5 mm
Lock type	2 Keys	Packaging content	
Ventilation	✓	Cables included	AC
Certification	PD 3.0 CE RoHS	Manual	✓
		Number of keys included	2 pc(s)



0766623715959



766623715959

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.