

Epson EB-L630SU data projector Standard throw projector 6000 ANSI lumens 3LCD WUXGA (1920x1200) White

Brand : Epson

Product code: V11HA29040

Product name : EB-L630SU



Epson EB-L630SU. Projector brightness: 6000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Fixed focal length: 1.18 cm, Zoom type: Auto. Video processing: 10 bit, Video colour modes: Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection. Serial interface type: RS-232C

Projector		Features	
Screen size compatibility *	1270 - 5080 mm (50 - 200")	HDCP	✓
Projection distance	0.9 - 3.5 m	Noise level *	38 dB
Projection distance (wide)	0.9 - 3.5 m	Country of origin	Philippines
Projector brightness *	6000 ANSI lumens	Password protection	✓
Projection technology *	3LCD	Multimedia	
Projector native resolution *	WUXGA (1920x1200)	Built-in speaker(s) *	✓
Contrast ratio (typical) *	2500000:1	RMS rated power	10 W
Native aspect ratio *	16:10	Number of built-in speakers	1
Number of colours	1.07 billion colours	Design	
Projector brightness (economic mode)	4200 ANSI lumens	Market positioning *	Presentation
Keystone correction, horizontal	-30 - 30°	Product type *	Standard throw projector
Keystone correction, vertical	-30 - 30°	Product colour *	White
Matrix size	1.7 cm (0.67")	Placement	Ceiling, Desktop
Light source		Cable lock slot	✓
Light source type *	Laser	Cable lock slot type	Kensington
Service life of light source *	20000 h	Display	
Service life of light source (economic mode)	30000 h	Built-in display *	✗
Lens system		Power	
Focus *	Manual	Power source *	AC
Fixed focal length	1.18 cm	Power consumption (typical) *	345 W
Zoom capability	✓	Power consumption (standby) *	0.3 W
Zoom type	Auto	Power consumption (economy mode)	258 W
Zoom ratio	1.35:1	AC input voltage	100-240 V
Throw ratio	0.80:1	AC input frequency	50 - 60 Hz
Horizontal lens shift range	-20 - 20%	Software	
Vertical lens shift range	-50 - 50%	Software support	via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol
Video		Operational conditions	
Analog signal format system *	Not supported	Storage temperature (T-T)	-10 - 60 °C
Full HD *	✓	Operating relative humidity (H-H)	20 - 80%
3D *	✗	Storage relative humidity (H-H)	10 - 90%
Video processing	10 bit	Weight & dimensions	
Video colour modes	Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection	Width	440 mm
Ports & interfaces		Depth	334 mm
USB 2.0 ports quantity *	2	Height	136 mm
USB 2.0 Type-B ports quantity	1	Weight *	8.4 kg
Audio (L/R) in *	1		
Serial interface type *	RS-232C		

Ports & interfaces		Weight & dimensions	
VGA (D-Sub) ports quantity *	3	Package width	540 mm
HDMI ports quantity *	3	Package depth	560 mm
DVI port *	✘	Package height	210 mm
Network		Package weight	12.3 kg
Ethernet LAN *	✓	Packaging content	
Ethernet LAN data rates	10,100,1000 Mbit/s	Remote control included *	✓
Wi-Fi *	✓	Batteries included	✓
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Cables included	AC
Miracast	✓	Manual	✓
Storage		Warranty card	✓
Card reader integrated *	✘	WLAN adapter included	✓
Features		Logistics data	
Noise level (economic mode)	27 dB	Quantity per pack	1 pc(s)
		Products per pallet	14 pc(s)
		Products per pallet (UK)	14 pc(s)
		Harmonized System (HS) code	85286200
		Other features	
		Supported network protocols	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink



8715946695358

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-JUN-2024. Prints or copies of Information are only valid on the printed Publication date