

HP M24m Conferencing Monitor

Brand: HP Product code: 678U5AA

Product name : M24m Conferencing Monitor

M24m Conferencing Monitor

HP M24m Conferencing Monitor:

Productivity all built-in

Welcome to a better conferencing experience. The integrated 5MP webcam, dual noise-canceling microphones, and built-in speakers makes this sleek 60,45 cm(23.8-inch) FHD monitor the centerpiece of your connected daily life. It's designed for ease and simplicity without compromising quality so you can feel as good as you look on every call.

HP M24m Conferencing Monitor. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting, Height adjustment. Product colour: Black












| Display | | Ergonomics | |
|--------------------------------|---|---|------------------------------|
| Display diagonal * | 60.5 cm (23.8") | VESA mounting * | √ |
| Display resolution * | 1920 x 1080 pixels | Panel mounting interface | 100 x 100 mm |
| HD type * | Full HD | Height adjustment * | √ |
| Native aspect ratio * | 16:9 | Height adjustment | 10 cm |
| Panel type * | VA | Swivelling | √ |
| Backlight type | Edge LED | Swivel angle range | -45 - 45° |
| Display brightness (peak) | 250 cd/m ² | Tilt angle range | -5 - 23° |
| Response time | 5 ms | Power | |
| Anti-glare screen | ✓ | | - |
| Screen shape * | Flat | Energy efficiency class (SDR) * | E |
| Supported graphics resolutions | 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1280 x 720 (HD 720), 720 x 400, 1280 x 800 (WXGA), 1280 x 1024 (SXGA), 800 x 600 (SVGA), 1440 x 900 (WXGA+), 640 x 480 (VGA), 1024 x 768 (XGA), 1600 x 900 | Energy consumption (SDR) per 1000 hours * | 16 kWh |
| | | Power consumption (typical) * | 30 W |
| | | Power consumption (standby) * | 0.5 W |
| | | Power consumption (max) | 120 W |
| | | AC input voltage | 100 - 240 V |
| Contrast ratio (typical) * | 1000:1 | AC input frequency | 50/60 Hz |
| Contrast ratio (dynamic) | 8000000:1 | Energy efficiency scale | A to G |
| Maximum refresh rate * | 75 Hz | Operational conditions | |
| Viewing angle, horizontal | 178° | Operating temperature (T-T) | 5 - 35 °C |
| Viewing angle, vertical | 178° | Operating relative humidity (H-H) | 20 - 80% |
| Pixel pitch | 0.2745 x 0.2745 mm | Storage relative humidity (H-H) | 5 - 95% |
| Pixel density | 93 ppi | , , , | |
| Horizontal scan range | 30 - 85 kHz | Packaging content | |
| Vertical scan range | 48 - 75 Hz | Stand included | ✓ |
| Display diagonal (metric) | 60.45 cm | Cables included | AC, USB Type-C to USB Type-C |
| Surface hardness | 3H | Weight & dimensions | |
| Colour depth | 8 bit | Width (with stand) | 539.5 mm |
| Colour gamut standard | sRGB | Depth (with stand) | 211.4 mm |
| Colour gamut | 99% | Height (with stand) | 523.4 mm |

| Performance | | Weight & dimensions | |
|---|------------------------------------|--|--------------------------------------|
| Low Blue Light technology Multimedia | ✓ | Weight (with stand) Width (without stand) | 6.3 kg 539.5 mm |
| Built-in camera * Megapixel (approx.) | √ 5 MP | Depth (without stand) Height (without stand) | 47.9 mm 372.2 mm |
| Design | | Packaging data | |
| Market positioning * Product colour * Introduction year Country of origin | Business Black 2022 China | Package width Package depth Package height Package weight | 596 mm 195 mm 416 mm 9.2 kg |
| Ports & interfaces | | Sustainability | |
| USB Type-A downstream ports quantity | 2 | European Product Registry for Energy Labelling (EPREL) code | 1222321 |
| USB Type-C downstream ports quantity | 1 | Brand-specific features | 107102260261 |
| USB Type-C DisplayPort Alternate Mode | √ | HP GTIN (EAN/UPC) Other features | 197192360361 |
| USB Power Delivery | ✓ | Weight | 6.3 kg |
| USB Power Delivery up to | 65 W | Height | 372.2 mm |
| HDMI * | ✓ | Width | 539.5 mm |
| HDMI ports quantity | 1 | Depth | 47.9 mm |
| HDMI version | 1.4 | | |
| DisplayPorts quantity | 1 | | |
| DisplayPort version | 1.2 | | |
| Audio output | ✓ | | |


























Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.