



## HDMI to DVI-D Cable

HDMI Male to DVI-D 24+1 Male, Dual Link, 1 m (3 ft.), Black  
Part No.: [322782](#)

---

Superior connections for quality digital video performance

The Manhattan HDMI to DVI-D Cable delivers the brightest, most accurate colors and sharpest detail when connecting a high-definition television, LCD or plasma display, digital satellite receiver, DVD player, digital projector or other DVI- or HDMI-equipped display devices. Manhattan HDMI to DVI-D Cable is engineered and constructed of quality materials to deliver dependable transmissions in digital video applications. Full foil and braided shielding, molded boots with strain relief, protective PVC jackets and gold-plated connections help provide maximum conductivity and clear, crisp signal transmissions with reduced EMI interference and distortion.

### Features:

- HDMI 19-pin male to DVI-D 24+1 male; gold plated connections
- Connects an HDMI video source to a DVI-D display
- Fully shielded to reduce EMI and other interference sources
- Supports existing HD (720p, 1080i and 1080p @ 60 Hz), enhanced (480p) and standard (NTSC or PAL) video formats
- Molded PVC boot
- Lifetime warranty

### Specifications:

#### Standards and Certifications

- Meets or exceeds existing HDMI and DVI-D standards
- Compatible with DVI-D dual link devices
- UL
- ISO9001

### Contacts

*For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).*

*All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.*

- One HDMI 19-pin male
- One DVI-D 24+1-pin male
- Molded PVC boot
- Shielded
- 30 AWG connectors

#### Cable

- Shielded
- Length: 1 m (3 ft)
- Current rating: 0.5 A DC
- Withstanding voltage: 300 V DC
- Insulation resistance: 5 MOhms
- Conductive resistance: 5 Ohms
- Thermal plastic casing

#### Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 5 – 90%

#### Package Contents

- HDMI to DVI-D Cable

