## ASUS ZenWiFi AX (XT9) AX7800 2er Set Schwarz Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Black 4 Internal

**Brand :** ASUS **Product code:** 90IG0740-MO3B30

Product name: ZenWiFi AX (XT9) AX7800 2er Set

Schwarz

ZenWiFi AX (XT9) AX7800 2er Pack, Black

ASUS ZenWiFi AX (XT9) AX7800 2er Set Schwarz. Product colour: Black, Antenna type: Internal, Product type: Mesh system. Wi-Fi band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), Wi-Fi standards: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Processor frequency: 1.7 GHz, Internal memory: 512 MB, Flash memory: 256 MB. AC adapter input voltage: 110 - 240 V, AC adapter frequency: 50 - 60 Hz, AC adapter output voltage: 12 V. Weight: 740 g





Design		Wireless LAN features	
Product type Product colour * LED indicators Antenna type *	Mesh system Black Power Internal	VPN support	Instant Guard VPN Client L2TP VPN Client OVPN VPN Client PPTP VPN Client WireGuard VPN Server IPSec VPN Server OVPN VPN Server PPTP VPN Fusion VPN Server WireGuard
Antennas quantity	6	Features	
Maximum coverage Reset button	264.77 m² ✓	Built-in processor	<b>√</b>
Wireless LAN features		Processor cores Processor frequency	2 1.7 GHz
Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)	Internal memory	512 MB
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Flash memory	256 MB
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Quality of Service (QoS) support Parental control Parental control features	✓ ✓ Custom profiles
WLAN data transfer rate (first band)	574 Mbit/s	Firmware upgradeable via	Auto upgrade wizard
WLAN data transfer rate (second band)	2402 Mbit/s	Operating modes	Wireless router mode, Access point mode
WLAN data transfer rate (third band)	4804 Mbit/s	Ports & interfaces	mode
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11g, IEEE 802.11n	Ethernet LAN (RJ-45) ports * Ethernet WAN	4 ✓
Security algorithms	WPA-Enterprise, WPA-PSK, WPA2- Enterprise, WPA2-PSK, WPA3-PSK, WPS	Power	
		AC adapter input voltage	110 - 240 V
IGMP snooping	1	AC adapter frequency	50 - 60 Hz
Dynamic DNS (DDNS)	✓	AC adapter output voltage	12 V
Guest access	✓	AC adapter output current	3 A
		Weight & dimensions	
		Weight	740 g
		Packaging content	
		AC adapter included Ethernet cable	1



4711081743958

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.