## **PHILIPS**

## Philips Evnia 8000 49M2C8900L/00 computer monitor 124.2 cm (48.9") 5120 x 1440 pixels Dual QHD QDOLED White

**Brand :** Philips

**Product family:** Evnia

Product code: 49M2C8900L/00

49" QC OLED War 4K Property PHILIPS

Product name: 49M2C8900L/00

Gaming Monitor 49M2C8900L QD OLED gaming monitor

Philips Evnia  $8000 \ 49M2C8900L/00$  computer monitor  $124.2 \ cm$  (48.9")  $5120 \ x$  1440 pixels Dual QHD QDOLED White:

Experience luxurious gaming with this monitor's colourful QD OLED display, incredible DisplayHDR $^{\text{TM}}$  TrueBlack 400 certification and booming DTS Sound $^{\text{M}}$  speakers. This monitor is likely to give you a gaming escapade that's hard to forget.

Philips Evnia 8000 49M2C8900L/00. Display diagonal: 124.2 cm (48.9"), Display resolution: 5120 x 1440 pixels, HD type: Dual QHD, Display technology: QDOLED, Response time: 0.03 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub. VESA mounting, Height adjustment. Product colour: White





Display		Ports & interfaces	
Display diagonal *	124.2 cm (48.9")	HDCP version	1.4/2.2/2.3
Display resolution *	pical) 250 cd/m² 0.03 ms  Curved 1800R 1000000:1 0 marketing Mega Infinity DCR  144 Hz 178° 11 178°	Ergonomics	
HD type * Native aspect ratio * Display technology * Panel type * Touchscreen * Display brightness (peak) Display brightness (typical) Response time Anti-glare screen Screen shape *		VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Swivelling Swivel angle range Tilt angle range Picture-in-Picture	100 x 100 mm  Kensington  12 cm  -20 - 20°  -5 - 15°
Screen curvature rating Contrast ratio (typical) * Dynamic contrast ratio marketing name Maximum refresh rate *		On Screen Display (OSD)  On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese,
Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Pixel density		Number of OSD languages Plug and Play LED indicators	Korean, Polish, Portuguese, Russian Swedish, Turkish, Ukrainian 21 ✓ Operation, Stand-by
Vertical scan range	48 - 144 Hz	Power	
Viewable size, horizontal Viewable size, vertical Display diagonal (metric) High Dynamic Range (HDR) supported	119.7 cm 33.9 cm 124.3 cm ✓	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Power consumption (typical) * Power consumption (standby) * Power consumption (off)	G G 156.5 W 0.5 W 0.3 W
High Dynamic Range (HDR) technology	DisplayHDR 400 True Black	AC input voltage AC input frequency	100 - 240 V 50/60 Hz

	Da	
2H 10 bit DCI-P3 99% 153.1% 127.4%	Power supply type	Internal
	Operational conditions	
	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 20 - 80% 0 - 3658 m 3658 - 12192 m
	Packaging content	
•	Stand included	✓
J	Cables included	AC, DisplayPort, HDMI, USB, USB
FreeSync Premium Pro 3-sided  Power Delivery 3.0  Separate sync  Mac OS X Windows 11/10/8.1/8	Remote control included Manual	Type-C to USB Type-C  ✓
	Weight & dimensions	
	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand)	1195 mm 359 mm 544 mm 14 kg 1195 mm 181 mm
	-	369 mm
1		10.8 kg
<b>X</b> 4 30 W DTS	Packaging data Package width Package depth Package height Package weight	1290 mm 475 mm 300 mm 19.4 kg
	Sustainability	
Gaming White Hg (mercury)	Sustainability compliance Sustainability certificates Doesn't contain	√ RoHS Mercury, PVC/BFR
/	Technical details	
	Compliance certificates	RoHS
<b>√</b>	Other features	
90 W  2 2.1 1 1.4  ✓	DCI-P3 coverage Picture-by-Picture (PbP) Exterior finish type Picture enhancement Sound enhancement technology Recyclable packaging material Regulatory Approvals  Speakers Delta E LowBlue mode	99%  Textured  SmartImage game  DTS  100%  CB, CE mark, FCC Class B, ICES-003, TUV/ISO9241-307, TUV-BAUART, EAC  7.5 W x 2 tweeters, 7.5 W x 2 woofers with airflow vents  2
	2H 10 bit DCI-P3 99% 153.1% 127.4% 125.2%   FreeSync Premium Pro 3-sided   Power Delivery 3.0   Mac OS X Windows 11/10/8.1/8	2H 10 bit 10 bit 10 cl-P3 199% 125.2% 125.2% 125.2% 126 127.4% 125.2% 127.4% 128.2% 128.2% 129.2% 120 bit



8712581803926

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.