



# APC Smart-UPS uninterruptible power supply (UPS) Line-Interactive 0.45 kVA 280 W 4 AC outlet(s)

Brand : APC

Product code: SC450RMI1U

Product name : Smart-UPS



APC Smart-UPS SC 450VA 230V - 1U Rackmount Tower


APC Smart-UPS. UPS topology: Line-Interactive, Output power capacity: 0.45 kVA, Output power: 280 W.

AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 108 VAh, Typical backup time at full load: 5.9 min. Form factor: Rackmount/Tower, Product colour: Grey, Rack capacity: 1U. Width: 432 mm, Depth: 383 mm, Height: 44 mm



Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	0.45 kVA	<b>Design</b>	
Output power *	280 W	Form factor *	Rackmount/Tower
Waveform *	Sine	Rack capacity	1U
Input operation voltage (min) *	151 V	Product colour *	Grey
Input operation voltage (max) *	302 V	LED indicators	Battery replacement
Input frequency *	50/60 Hz	Certification	C-tick, CE, GOST, VDE, PEP, EOL
Automatic Voltage Regulation (AVR)	✓	<b>Operational conditions</b>	
Surge energy rating	320 J	Operating temperature (T-T)	0 - 40 °C
Hold time (min)	4 ms	Storage temperature (T-T)	-15 - 45 °C
Hold time (max)	8 ms	Operating relative humidity (H-H)	0 - 95%
Noise level	38 dB	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Network	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	<b>Technical details</b>	
Audible alarm modes	Low battery alarm, Overload alarm	Sustainability certificates	RoHS
Auto-restart	✓	Compliance certificates	RoHS
<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
AC outlet types	C13 coupler	Width	432 mm
Power plug	C14 coupler	Depth	383 mm
AC outlets quantity	4 AC outlet(s)	Height	44 mm
Number of output IEC jumpers	2	Weight	10.2 kg
Serial interface	✓	Package width	476 mm
Serial interface type	RS-232	Package depth	589 mm
Serial ports quantity	1	Package height	164 mm
<b>Battery</b>		Package weight	11.7 kg
Battery technology	Sealed Lead Acid (VRLA)		


Battery		Packaging data	
Battery capacity	108 VAh	Rack mount kit	✓
Typical backup time at full load	5.9 min	Cables included	RS-232
Typical backup time at half load	19.4 min	Manual	✓
Battery life (max)	5 year(s)	Software CD	✓
Battery recharge time	5 h	<b>Logistics data</b>	
Hot-swap battery	✓	Products per pallet	24 pc(s)
		Harmonized System (HS) code	85078000
		<b>Other features</b>	
		Nominal output voltage	230 V



0731304222712



731304222712



0731304222729



731304222729



0071090238727



071090238727

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.