

## TP-Link Archer MR400 wireless router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) 4G Black

Brand : TP-Link Product code: ARCHER MR400

**Product name:** Archer MR400

- Cutting-edge 4G network share internet access with up to 64 Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- AC1200 Wi-Fi creates simultaneous dual band Wi-Fi networks, with maximum speeds of up to 300 Mbps on the 2.4 GHz band and 867 Mbps on the 5 GHz band
- Plug a SIM card and play no configurations needed, compatibility for SIM cards in 100+ countries are assured by years of field tests
- Two detachable advanced LTE antennas enjoy stable and efficient connections to every device thanks to the two external antennas
- Wi-Fi router mode plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection
- 3x 10/100Mbps LAN, 1x 10/100Mbps LAN/WAN, SIM, 802.11ac/n/a/b/g/n, 2.4/5 GHz, 202x141x33.6 mm





WAN connection		Protocols	
Ethernet WAN * SIM card slot * 3G/4G USB modem compatibility *	1 1	DHCP client DHCP server Supported network protocols	√ √ IPv4, IPv6
Wireless LAN features		Design	
Wi-Fi band * Top Wi-Fi standard * WLAN data transfer rate (max) * Wi-Fi standards	Dual-band (2.4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) 867 Mbit/s 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Product colour Wall mountable LED indicators On/off switch Product type *	Black  LAN, Power, Status, WLAN  Tabletop router
WLAN data transfer rate (first band) WLAN data transfer rate (second	•	Packaging content	
band) Network	867 Mbit/s	Cables included AC adapter included Quick installation quide	LAN (RJ-45) ✓
Ethernet LAN *	From Etherson	Antenna	•
Ethernet LAN interface type * Ethernet LAN data rates Cabling technology Networking standards	Fast Ethernet 10,100 Mbit/s 10/100Base-T(X) IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE	Antenna design * Antennas quantity Detachable antenna(s) Transmit power	Internal & external 2  ✓ <20dBm(2.4GHz), <23dBm(5GHz)
Port forwarding	802.11n	Features	
Dynamic DNS (DDNS)	<b>√</b>	Certification	CE, RoHS
VPN tunnels quantity	10	Power	
VPN Passthrough VPN support	PPTP, L2TP, IPSec	Power source type * Output voltage	DC 12 V
Mobile network		Output current	1.5 A
Mobile network generation		Operational conditions	
2G standards 3G standards 4G standard GSM bands supported UMTS bands supported	Edge, GPRS, GSM DC-HSPA+, HSPA, HSPA+, UMTS LTE 850,900,1800,1900 MHz 900,2100 MHz	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90%

Mobile network		System requirements	
4G bands supported	800,900,1800,2100,2600 MHz		Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP
Ports & interfaces		Windows energting systems	
Ethernet LAN (RJ-45) ports * USB port *	3 <b>X</b>	Windows operating systems supported	
Management features		ti.	Professional x64
Web-based management Quality of Service (QoS) support Reset button	√ <b>×</b>	Linux operating systems supported Mac operating systems supported Mac compatibility	<b>4 4 4</b>
WPS push button	<b>,</b>	Weight & dimensions	
Security		Width	174 mm
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Depth Height	124.5 mm 33.5 mm
Firewall	1	Packaging data	
Guest access		Package width	307 mm
Access Control List (ACL)	✓	Package depth	223 mm
Stateful Packet Inspection (SPI)	✓	Package height	70 mm
DoS attack prevention	✓	Package weight	670 g
		Package type	Box

