## D-Link DPE-301GI PoE adapter Fast Ethernet, Gigabit Ethernet

Brand : D-Link

Product name : DPE-301GI

Product code: DPE-301GI

## 1-Port Gigabit PoE Injector, White

D-Link DPE-301GI. Ethernet interface type: Fast Ethernet, Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u. Product colour: White, Certification: CE, FCC, VCCI, RCM. Output power: 32.4 W, AC adapter input voltage: 100 - 240 V, AC adapter frequency: 50/60 Hz. Weight: 70 g, Dimensions (WxDxH): 109.8 x 62.2 x 24.5 mm. Package width: 153 mm, Package depth: 213 mm, Package height: 68 mm





Network		Packaging data	
Ethernet interface type Ethernet LAN data rates	Fast Ethernet, Gigabit Ethernet	Package width	153 mm 213 mm
	10,100,1000 Mbit/s	Package depth	
Power over Ethernet (PoE)		Package height	68 mm
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u	Package weight	398 g
Features		Packaging content Number of products included	1 pc(s)
Product colour	White	·	1 pc(s)
Rack mounting		Logistics data	
LED indicators	1	Shipping (inner) case length	32.6 cm
Certification	CE, FCC, VCCI, RCM	Shipping (inner) case width	23.3 cm
Ports & interfaces		Shipping (inner) case height	36 cm
		Shipping (inner) case net weight	4.1 kg
Ethernet LAN (RJ-45) ports	2	Products per shipping (inner) case	10 pc(s)
DC-in jack	4	Pallet gross weight (air)	297.8 kg
Power		Master (outer) cases per pallet (air)	60 pc(s)
Output power	32.4 W	Products per pallet (air)	600 pc(s)
AC adapter input voltage	100 - 240 V	Pallet gross length	120 cm
AC adapter frequency	50/60 Hz	Pallet gross width	110 cm
Output current	0.6 A	Pallet height (air)	194 cm
Operational conditions		Pallet gross weight (sea)	297.8 kg
Operating temperature (T-T)	0 - 50 °C	Master (outer) cases per pallet (sea)	
Operating temperature (T-T)	32 - 122 °F	Products per pallet (sea)	600 pc(s)
Operating relative humidity (H-H)	52 - 122 F 5 - 95%	Pallet height (sea)	194 cm
Storage temperature (T-T)	-30 - 70 °C	Shipping (inner) case gross weight	4.63 kg
Storage relative humidity (H-H)	-30 - 70 °C 5 - 95%	Harmonized System (HS) code	85044095
	2 - 22 %		
Weight & dimensions			
Weight	70 g		
Dimensions (WxDxH)	109.8 x 62.2 x 24.5 mm		





790069416668

0790069416668

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.