EIZO FlexScan EV2360-WT LED display 57.1 cm (22.5") 1920 x 1200 pixels WUXGA White

Brand : EIZO   **Product family:** FlexScan   **Product code:** EV2360-WT

Product name : EV2360-WT

22.5"/57.2 cm, IPS 1920 x 1200 px, 16:10, 250 cd/m2, 5 ms, sRGB, DispalyPort, VGA, HDMI, USB 3.0, 11 kWh/1000h, C

EIZO FlexScan EV2360-WT. Display diagonal: 57.1 cm (22.5"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: White

Display

Display diagonal *	57.1 cm (22.5")
Display resolution *	1920 x 1200 pixels
HD type *	WUXGA
Native aspect ratio *	16:10
Display technology *	LED
Panel type *	IPS
Backlight type	LED
Touchscreen *	✘
Display brightness (typical)	250 cd/m²
Response time	5 ms
Screen shape *	Flat
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)
Contrast ratio (typical) *	1000:1
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.78 million colours
Pixel pitch	0.254 x 0.248 mm
Pixel density	101 ppi
Horizontal scan range	31 - 75.5 kHz
Vertical scan range	59 - 61 Hz
Viewable size, horizontal	48.8 cm
Viewable size, vertical	29.7 cm
Viewable size diagonal	57.2 cm
Colour gamut standard	sRGB

Ports & interfaces

HDMI *	✔
DisplayPorts quantity	1
Audio input	✔
Headphone out *	✔
Headphone connectivity	3.5 mm
HDCP	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Height adjustment *	✔
Height adjustment	14 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	0 - 344°
Tilt adjustment	✔
Tilt angle range	-5 - 35°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Swedish

Power

Energy efficiency class (SDR) *	C
Energy consumption (SDR) per 1000 hours *	11 kWh
Power consumption (typical) *	10.5 W
Power consumption (standby) *	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Performance		**Power**	
NVIDIA G-SYNC *	✘	Energy efficiency scale	A to G
AMD FreeSync *	✘	**Operational conditions**	
Flicker-free technology	✔	Operating temperature (T-T)	5 - 35 °C
Multimedia		Operating relative humidity (H-H)	20 - 80%
Built-in speaker(s) *	✔	**Packaging content**	
Number of speakers	2	Stand included	✔
RMS rated power	2 W	Cables included	AC, DisplayPort, USB
Design		**Weight & dimensions**	
Market positioning *	Business	Width (with stand)	499 mm
Product colour *	White	Depth (with stand)	233 mm
Frameless design	✔	Height (with stand)	333.9 mm
Certification	CE, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC, BIS, BSMI, EAC	Weight (with stand)	5.5 kg
		Width (without stand)	499 mm
		Depth (without stand)	53.6 mm
		Height (without stand)	321.3 mm
		Weight (without stand)	3.4 kg
		Sustainability	
		Sustainability compliance	✔
Ports & interfaces		Sustainability certificates	ENERGY STAR, EPEAT Climate +, EPEAT Silver, TCO
Built-in USB hub *	✔	European Product Registry for Energy Labelling (EPREL) code	346698
USB hub version	3.2 Gen 1 (3.1 Gen 1)	**Logistics data**	
USB upstream port type	USB Type-B	Harmonized System (HS) code	85285210
Number of upstream ports	1		
USB Type-A downstream ports quantity	2		
VGA (D-Sub) ports quantity	1		
DVI port	✘		

4995047055204

0690592048230

690592048230