PHILIPS

Philips 6000 series 45B1U6900C/00 LED display 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD Black

Brand: Philips

Product family: 6000 series

Product code: 45B1U6900C/00

Product name: 45B1U6900C/00

.00900C/00



Curved Business Monitor 45B1U6900C 32:9 SuperWide curved monitor with USB-C

Philips 6000 series 45B1U6900C/00 LED display 113 cm (44.5") 5120×1440 pixels UltraWide Dual Quad HD Black:

This Philips USB-C multi-purpose monitor offers clutter-free setup. With a single cable you can view smooth, high-resolution video, transfer data and charge your laptop. The headphone holder brings cable management to the next level.

Philips 6000 series 45B1U6900C/00. Display diagonal: 113 cm (44.5"), Display resolution: 5120×1440 pixels, HD type: UltraWide Dual Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178° , Viewing angle, vertical: 178° . Built-in Speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black









Display		Ports & interfaces	
Display diagonal *	113 cm (44.5")	HDCP version	1.4/2.2
Display resolution *	5120 x 1440 pixels	AC (power) in	✓
HD type *	UltraWide Dual Quad HD	Network	
Native aspect ratio *	32:9	Ethernet LAN	√
Display technology *	LED		•
Panel type *	VA	Ergonomics	
Backlight type	W-LED	VESA mounting *	✓
Touchscreen *	×	Panel mounting interface	100 x 100 mm
Display brightness (typical)	450 cd/m²	Cable lock slot *	✓
Response time	4 ms	Cable lock slot type	Kensington
Anti-glare screen	✓	Height adjustment *	✓
Screen shape *	Curved	Height adjustment	15 cm
Screen curvature rating	1500R	Swivelling	✓
Contrast ratio (typical) *	3000:1	Swivel angle range	-45 - 45°
Contrast ratio (dynamic)	80000000:1	Tilt adjustment	✓
Dynamic contrast ratio marketing	SmartContrast	Tilt angle range	-5 - 15°
name		Picture-in-Picture	✓
Maximum refresh rate *	75 Hz	On Screen Display (OSD)	✓
Viewing angle, horizontal	178°		Simplified Chinese, Traditional
Viewing angle, vertical	178°		Chinese, Czech, German, Dutch,
Display number of colours *	16.7 million colours	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese,
Pixel pitch	0.2124 x 0.2124 mm		Korean, Polish, Portuguese, Russian,
Pixel density	120 ppi		Swedish, Turkish, Ukrainian
Horizontal scan range	30 - 114 kHz	Number of OSD languages	21
Vertical scan range	48 - 75 Hz	Plug and Play	1
Viewable size, horizontal	108.7 cm	LED indicators	Operation, Stand-by
Viewable size, vertical	30.6 cm	Power	
Display diagonal (metric)	113 cm	Energy efficiency class (SDR) *	G
High Dynamic Range (HDR) supported	✓	Power consumption (typical) *	46.3 W

Display		Power	
High Dynamic Range (HDR)	DisplayHDR 400	Power consumption (standby) *	0.3 W
technology		Power consumption (PowerSave)	36.5 W
DDC/CI	√	AC input voltage	100 - 240 V
Haze rate	25%	AC input frequency	50 - 60 Hz
Surface hardness	2H	Power supply type	Internal
Colour depth	8 bit	Operational conditions	
sRGB coverage (typical)	123%	Operating temperature (T-T)	0 - 40 °C
NTSC coverage (typical)	107%	Storage temperature (T-T)	-20 - 60 °C
Display sRGB	✓	Operating relative humidity (H-H)	20 - 80%
Performance		Operating altitude	0 - 3658 m
VESA Adaptive Sync support	✓	Non-operating altitude	0 - 12192 m
Component video sync	Separate sync		·
Flicker-free technology	✓	Packaging content	
HBR3 support	✓	Stand included	✓
Compatible operating systems	Mac OS X, Windows 11/10/8.1/8	Cables included	HDMI, DisplayPort, USB Type-C, AC
Multimedia		Manual	✓
Built-in speaker(s) *	√	Bundled software	SmartControl
Built-in speaker(s) ** Built-in camera *	×	Weight & dimensions	
Number of speakers	2	Width (with stand)	1085 mm
·	2	Depth (with stand)	238 mm
Design		Height (with stand)	515 mm
Market positioning *	Business	Weight (with stand)	12.8 kg
Product colour *	Black	Width (without stand)	1085 mm
Frameless design	1	Depth (without stand)	158 mm
Front bezel colour	Black	Height (without stand)	337 mm
Feet colour	Black	Weight (without stand)	9.75 kg
Ports & interfaces		Packaging data	
Ports & interfaces Built-in USB hub *	√	Packaging data Package width	1180 mm
	✓ 3.2 Gen 1 (3.1 Gen 1)	Package width	1180 mm 535 mm
Built-in USB hub *		Package width Package depth	1180 mm 535 mm 235 mm
Built-in USB hub * USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package width Package depth Package height	535 mm
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2	Package width Package depth Package height Package weight	535 mm 235 mm
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C	Package width Package depth Package height Package weight Sustainability	535 mm 235 mm 17.1 kg
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2	Package width Package depth Package height Package weight Sustainability Sustainability certificates	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1	Package width Package depth Package height Package weight Sustainability	535 mm 235 mm 17.1 kg
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2	Package width Package depth Package height Package weight Sustainability Sustainability certificates	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85%
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP)	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85%
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85%
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1 ✓ ✓ 100 W	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI *	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage 100%
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified;
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 2
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 2
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode LowBlue mode	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 2
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode LowBlue mode Philips SmartUniformity	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 2
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Mean time between failures (MTBF)	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 2 ✓ ✓ 7 93 - 105% 70000 h
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	3.2 Gen 1 (3.1 Gen 1) USB Type-B, USB Type-C 2 1 1 4 1	Package width Package depth Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode LowBlue mode Philips SmartUniformity	535 mm 235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 2



8712581797454

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.