



## HDMI Repeater

HDMI Signal Repeater, Regenerates 4K Video and Lossless Audio up to 40 m (131 ft.)

Part No.: **207621**

---

Easily extend your HDMI signal.

The Manhattan HDMI Repeater extends the range of an HDMI signal by decoding and then regenerating it at up to 4K@60Hz resolution from virtually any HDMI source (Playstation, Xbox, Blu-ray player, satellite receiver, digital recorder, etc.) using existing HDMI cables. Designed for plug-and-play installation, this Repeater boosts weak signals to reduce or eliminate picture noise, degradation or sparkles on an HD display or projector. Includes an additional USB power port for video sources that doesn't provide enough power.

### Flexible Solution for Many A/V Applications

The Manhattan HDMI Repeater is ideal for trade shows, classrooms, home theater, conference rooms, business office and retail applications. It offers the flexibility of locating a high-definition display or projector at up to 40 m (131 ft.) from the HDMI source. For best performance, place this Repeater near the middle of the distance (15 to 20 m, or 49 to 65 ft.) and use high-quality twisted pair HDMI cables (longer distances and inferior cables may degrade performance).

### Quality Construction and Easy Installation

HDCP compliant with HDMI, HDCP 2.2 and DVI 1.0, this HDMI Repeater is tested to guarantee performance and reliability. It installs quickly without additional software, hardware or power sources (in most cases).

### Features:

- Boosts high-definition signal over HDMI cables for 4K performance up to 40 m / 131 ft.
- Delivers a sharp, clear signal from a Playstation, Xbox, Blu-ray player, set-top box, satellite receiver or other video source
- Supports 4K@60Hz resolution as well as HDR YUV 4:4:4, HD 3-D video and Deep Color (24-bits/pixel)
- Fully HDCP compliant to protect high-definition content transmission and ensure quality reception
- Supports video amplifier bandwidth up to 6.0 Gbps (for 4K@60Hz)
- Plug and play — requires no installation, configuration or external power

- Included Micro-B USB cable can be connected for the extra boost needed to supply sufficient power to the video-source port
- Gold-plated contacts
- Three-Year Warranty

## Specifications:

### Standards and Certifications

- HDCP 2.2
- DVI 1.0
- CE
- FCC
- RoHS2

### Connections

- One HDMI female (input)
  - Cable length: 5-25 m (15-80 ft.)
- One HDMI female (output)
  - Cable length: 1-15 m (3-50 ft.)
- One Micro-B USB (input), additional power

### Signal Input/Output

- Input video signal: 0.5 – 1.0 V p-p
- Input DDC signal: 5 V p-p (TTL)
- Maximum single-link range: 4096 x 2160, 4K@60Hz
- Output video: HDCP 2.2, DVI 1.0
- Frequency: 6.0 Gbps / 600 MHz

### Video Resolutions

- VGA: 640 x 480, 800 x 600, 1024 x 768, 1920 x 1200
- DTV/HDTV/UHDTV: 480i/480p/576i/576p/720p/1080i/1080p/4K@30Hz/4K@60Hz
- 1080p-capable up to 50m
- 4K@30Hz-capable up to 40m
- 4K@60Hz-capable up to 25m

### Physical

- Dimensions: 50 x 28 x 14 mm (2 x 1 x 0.6 in.)
- Weight: 0.02 kg (0.04 lbs.) without cable
- Cable length: 0.7 m (28 in.)

### Operating Environment

- Operation Temperature: 32 – 104°F (0 – 40°C)
- Storage Temperature: -4 – 140°F (-20 – 60°C)
- Humidity (noncondensing): 0 – 96%

### Package Contents

- HDMI Repeater

- Micro-B USB Cable
- Quick Install Guide

