



Make It Yours.

FLEX YOUR GRAPHICS MUSCLE



Flex Your Graphics Muscle

The Cooler Master Riser Cable PCIe 4.0 x16 - 300mm is designed for greater data transmission efficiency, maximum flexibility and durability. High quality plastics grant increased cable flexibility and strength for the tightest PCI card installations, while the heavy-duty shielding prevents electromagnetic interference from degrading signal quality. The multi-layer coated PCB provides the best-in-class cable flex, moisture resistance and performance under high thermal loads.

FEATURES

PCIe 4.0 Compatible:

While Providing twice the bandwidth of PCIe 3.0, the Gen 4.0 riser cable remains backwards compatible with a maximum transfer rate of over 64Gb/s (bi-directional) and fully supports the 16GT/s bit rate of PCIe 4.0 devices.

Ultra Durable PCB:

The multi-layer coated PCB provides best-in-class cable flex, moisture resistance, and performance under high thermal loads.

Heavy Duty Shielding:

EMI shielded 30 AWG tinned copper wires ensure minimal signal delay and electromagnetic interference-free operation.

Gold-Plated Pin Connections:

Gold-plated PCI pin are rated 400g of retention force per contact pairs, ensuring maximum product lifespan and durability.

Protective ABS Casing:

UV resistant ABS casing protects cable connection points from rough handling.

Ultra-Flexible Cable Sleeves:

TPE cable sleeves allow for maximum flexibility and durability for the tightest cable routing jobs.

SPECIFICATIONS & PACKING INFORMATION

Product Number	MCA-U000C-KPCI40-300
Product Name	Riser Cable PCIe 4.0 x16 - 300mm
Units per package	1 unit per package
Available color	Black/Purple
Compatibility	PCIe 4.0 and older
CE Certificate Number	BKC210933AC
Component Materials	PCBA, Tinned Copper Wire 30 AWG
Insulation Materials	PE, TPE
Other Materials	ABS, Nickel, Gold, PP, Brass
Connectors	PCIe x16 Male to PCIe x16 90° Female
Cable Length	300mm (11.8in)
Contact Current Rating	1.1A per contact pin
Max Voltage Rating	30V
Working Voltage / Current	DC 12v / 5A
PCB / Wire UL Numbers	E189572 / E252840
Operating Temperature	-20° to +100° Celsius
Net Weight	144 g
Gross Weight	208 g
Warranty	1 year

EAN code	4719512123386 (外销) 6928968314844 (内销)
UPC code	884102095702
Carton Net Weight	2.88 kg (20pcs per carton)
Carton Gross Weight	4.70 kg (20pcs per carton)
Retail box dimension (L x W x H)	243mm x 155mm x 23mm
Carton dimension (L x W x H)	360mm x 257mm x 350mm

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	12320	56	N/A
40'	24640	56	N/A
40 HQ	29040	66	N/A